

Foreman - Bug #2562

Hosts created with wrong listen address

05/26/2013 04:27 AM - Ryan Davies

Status:	Closed	
Priority:	Normal	
Assignee:		
Category:	VM management	
Target version:	1.2.0	
Difficulty:		Fixed in Releases:
Triaged:		Found in Releases:
Bugzilla link:		Red Hat JIRA:
Pull request:		
Description Setting the listen address for new domains to 0 is breaking libvirt's API standard, http://libvirt.org/formatdomain.html#elementsGraphics Changed lib/foreman/model/libvirt.rb#console: vm.update_display(:password => password, :listen => '0') to vm.update_display(:password => password, :listen => '0.0.0.0') The websocket still works (and starts working for existing systems), and virt-manager starts working again (For newly defined machines) See pull request https://github.com/theforeman/foreman/pull/626		

Associated revisions

Revision 710dfa86 - 05/30/2013 09:41 AM - Ryan Davies

fixes #2562 libvirt domain listen address, add libvirt_default_console_address setting

Revision c8151d16 - 05/30/2013 12:51 PM - Ryan Davies

fixes #2562 libvirt domain listen address, add libvirt_default_console_address setting
(cherry picked from commit 710dfa86835e7b8b430cf59646a7888746c3b0bc)

History

#1 - 05/30/2013 09:41 AM - Dominic Cleal

- Status changed from New to Ready For Testing
- Priority changed from High to Normal

<https://github.com/theforeman/foreman/pull/626>

#2 - 05/30/2013 10:17 AM - Ryan Davies

- Status changed from Ready For Testing to Closed
- % Done changed from 0 to 100

Applied in changeset [710dfa86835e7b8b430cf59646a7888746c3b0bc](https://github.com/theforeman/foreman/pull/626).