

## Foreman - Bug #26381

### In Ovirt: You can create a disk with empty disk interface property.

03/17/2019 03:59 PM - Shimon Shtein

<b>Status:</b> Closed	
<b>Priority:</b> Normal	
<b>Assignee:</b>	
<b>Category:</b> Compute resources - oVirt	
<b>Target version:</b>	
<b>Difficulty:</b>	<b>Fixed in Releases:</b> 1.24.0
<b>Triaged:</b> No	<b>Found in Releases:</b>
<b>Bugzilla link:</b>	<b>Red Hat JIRA:</b>
<b>Pull request:</b> <a href="https://github.com/foreman/foreman/pull/7040">https://github.com/foreman/foreman/pull/7040</a>	
<b>Description</b>	
This will lead to:	
<pre>Failed to create a compute oris ovirt4 (oVirt) instance shim-irvin-preite.dummy: Fault reason is "Invalid value". Fault detail is "The string '' isn't a valid value for the 'DiskInterface' enumerated type. Valid values are: 'ide', 'virtio_scsi', 'virtio', 'spapr_vscsi'.". HTTP response code is 400</pre>	
exception.	
We should remove an empty Disk interface option from the UI.	

#### Associated revisions

##### Revision 6a05dfe2 - 10/03/2019 04:24 PM - Baptiste Agasse

Fixes #26381 - oVirt set default disk interface

#### History

##### #1 - 09/30/2019 02:12 PM - Baptiste Agasse

- Pull request <https://github.com/foreman/foreman/pull/7040> added

##### #2 - 10/03/2019 04:24 PM - The Foreman Bot

- Fixed in Releases 1.24.0 added

##### #3 - 10/03/2019 05:01 PM - Anonymous

- Status changed from New to Closed

Applied in changeset [6a05dfe234889a1e573835e843111659da284bff](#).