

## Foreman - Bug #26576

### Puppet class parameter type ignored if Boolean=false, ignores updates

04/10/2019 12:55 PM - Jacek Mierzwa

|   |                                  |
|---|----------------------------------|
| <b>Status:</b> New  |                                  |
| <b>Priority:</b> Normal   |                                  |
| <b>Assignee:</b>  |                                  |
| <b>Category:</b> Puppet integration   |                                  |
| <b>Target version:</b>  |                                  |
| <b>Difficulty:</b>  | <b>Fixed in Releases:</b>        |
| <b>Triaged:</b> No  | <b>Found in Releases:</b> 1.21.0 |
| <b>Bugzilla link:</b>   | <b>Red Hat JIRA:</b>             |
| <b>Pull request:</b>  |                                  |
| <b>Description</b>  |                                  |
| Please consider following Puppet class  |                                  |
| <pre>class class1 (<br/>  \$param1 = true,<br/>  \$param2 = 'something',<br/>  Boolean \$param3 = true,<br/>  \$param4 = false<br/>) {<br/>}</pre>                        |                                  |
| Current release is having issues reading param4 type.<br>While param1,2,3 are read correctly (boolean-string-boolean), param4 is imported into Foreman <b>as string</b> . |                                  |
| Moreover, let's say we change \$param1 default type to string:  |                                  |
| <pre>class class1 (<br/>  \$param1 = 'true',<br/>  \$param2 = 'something',<br/>  Boolean \$param3 = true,<br/>  \$param4 = false<br/>) {<br/>}</pre>                      |                                  |
| Foreman <b>does not detect this change</b> , param1 stays boolean.  |                                  |