

## Foreman - Feature #26955

### allow to set boot settings via environment variables

06/04/2019 05:08 PM - Timo Goebel

<b>Status:</b>	Closed	
<b>Priority:</b>	Normal	
<b>Assignee:</b>	Timo Goebel	
<b>Category:</b>	Settings	
<b>Target version:</b>	1.23.0	
<b>Difficulty:</b>		<b>Fixed in Releases:</b> 1.23.0
<b>Triaged:</b>	Yes	<b>Found in Releases:</b>
<b>Bugzilla link:</b>		<b>Red Hat JIRA:</b>
<b>Pull request:</b>	<a href="https://github.com/foreman/foreman/pull/6826">https://github.com/foreman/foreman/pull/6826</a>	
<b>Description</b>		
For running Foreman in a container, it would be beneficial to allow setting the boot settings via environment variables.		

#### Associated revisions

**Revision 47aca03d - 06/10/2019 01:54 PM - Timo Goebel**

fixes #26955 - load boot settings from env variables

#### History

**#1 - 06/04/2019 06:24 PM - The Foreman Bot**

- Status changed from New to Ready For Testing
- Assignee set to Timo Goebel
- Pull request <https://github.com/foreman/foreman/pull/6826> added

**#2 - 06/10/2019 01:54 PM - Ohad Levy**

- Target version set to 1.23.0
- Fixed in Releases 1.23.0 added

**#3 - 06/10/2019 02:02 PM - Timo Goebel**

- Status changed from Ready For Testing to Closed

Applied in changeset [47aca03d3f3be870aab808b58480f281863de766](#).