

## Foreman - Bug #28203

### Audits permantly changing with foreman in cluster deployment

11/05/2019 02:36 PM - Alexandre Barth

<b>Status:</b> Resolved	
<b>Priority:</b> Normal	
<b>Assignee:</b>	
<b>Category:</b> Audit Log	
<b>Target version:</b>	
<b>Difficulty:</b>	<b>Fixed in Releases:</b>
<b>Triaged:</b> No	<b>Found in Releases:</b> 1.23.0
<b>Bugzilla link:</b>	<b>Red Hat JIRA:</b>
<b>Pull request:</b>	
<b>Description</b>	
<p>I use foreman in cluster mode with two nodes, foreman1.mydomain.com and foreman2.mydomain.com foreman_url and unattended_url settings are set to http(s)://foreman.mydomain.com, wich is load balanced to foreman1.mydomain.com and foreman2.mydomain.com servers. In the audit page, every 30 mn entries are created for updated settings unattended_url and foreman_url : Default <a href="http://foreman1.mydomain.com">http://foreman1.mydomain.com</a> <a href="http://foreman2.mydomain.com">http://foreman2.mydomain.com</a> Default <a href="http://foreman2.mydomain.com">http://foreman2.mydomain.com</a> <a href="http://foreman1.mydomain.com">http://foreman1.mydomain.com</a> etc ... Audits page in foreman take minutes to load, have to manually clear these entries from non stop growing database.</p>	

#### History

#1 - 11/17/2019 09:56 AM - Tomer Brisker

- Category set to Audit Log

#2 - 04/02/2020 02:35 PM - Alexandre Barth

My bad, solved using cluster fqdn in --foreman-foreman-url foreman-installer parameter instead of --foreman-serveraliases

#3 - 04/02/2020 02:35 PM - Alexandre Barth

- Status changed from New to Resolved