

## Foreman - Bug #3070

### default\_template\_url() in PXE Default File creates https URL for kickstart instead of http

09/11/2013 09:21 AM - Sebastian Hutter

<b>Status:</b> Closed	
<b>Priority:</b> Normal	
<b>Assignee:</b>	
<b>Category:</b> Templates	
<b>Target version:</b>	
<b>Difficulty:</b>	<b>Fixed in Releases:</b>
<b>Triaged:</b> No	<b>Found in Releases:</b>
<b>Bugzilla link:</b>	<b>Red Hat JIRA:</b>
<b>Pull request:</b>	
<b>Description</b>	
Using the provisioning template PXE Default File to distribute host group based Kickstart configurations over PXE/TFTP an https URL gets created for the ks parameter.	
ks= <code>*https*://foreman.lzlabs.ch/unattended/template/LzLabs - Parallels Kickstart/CentOS Parallels VM</code> instead of ks= <code>*http*://foreman.lzlabs.ch/unattended/template/LzLabs - Parallels Kickstart/CentOS Parallels VM</code>	
see the template Pxe Default File here: <a href="http://pastebin.com/kRxtggq3">http://pastebin.com/kRxtggq3</a>	

#### History

**#1 - 09/11/2013 09:28 AM - Dominic Cleal**

- Category set to Templates

**#2 - 04/20/2021 12:44 PM - Leos Stejskal**

- Status changed from New to Closed

I'm closing the issue,  
it have been here for some time and I wasn't able to reproduce it on the latest version.  
If you believe that the issue is still relevant feel free to reopen it.

#### Files

foreman-debug-PtKfU.tar.xz	63.6 KB	09/11/2013	Sebastian Hutter
----------------------------	---------	------------	------------------