

Foreman - Bug #30990

GRT and HRT should use curl with --fail to avoid executing html code on 5xx responses

10/05/2020 06:28 PM - Marek Hulán

Status:	New	
Priority:	Normal	
Assignee:		
Category:	Host registration	
Target version:		
Difficulty:		Fixed in Releases:
Triaged:	Yes	Found in Releases:
Bugzilla link:		Red Hat JIRA:
Pull request:		
Description		
Related issues:		
Related to Foreman - Feature #30696: Improve the error output in global regis...		New

History

#1 - 10/05/2020 06:29 PM - Marek Hulán

- Related to Feature #30440: Simple & automatic host registration WF added

#2 - 10/20/2020 12:41 PM - Leos Stejskal

But using --fail means we won't show user errors any errors, they won't see what (and where) went wrong.

#3 - 11/08/2020 03:14 PM - Tomer Brisker

- Category set to Host registration

#4 - 06/04/2021 08:30 AM - Leos Stejskal

- Related to deleted (Feature #30440: Simple & automatic host registration WF)

#5 - 08/09/2021 12:54 PM - Leos Stejskal

- Related to Feature #30696: Improve the error output in global registration template added

#6 - 08/09/2021 12:55 PM - Leos Stejskal

This could be covered in <https://projects.theforeman.org/issues/30696>

#7 - 08/09/2021 12:56 PM - Leos Stejskal

- Triaged changed from No to Yes