

Foreman - Bug #31296

Document host import from compute resource via API

11/11/2020 09:22 AM - Anton Nesterov

Status: New	
Priority: Normal	
Assignee:	
Category: API	
Target version:	
Difficulty: easy	Fixed in Releases:
Triaged: No	Found in Releases:
Bugzilla link:	Red Hat JIRA:
Pull request:	
Description	
<p>I figured that it's possible to use POST to /api/hosts endpoint to import hosts from a compute resource.</p> <pre>{"host": {"compute_resource_id": 1, "uuid": "e6cd2ca9-312b-4b35-809c-84ac72c5f182", "hostgroup_id": 3, "location_id": 2, "organization_id": 1}}</pre>	
<p>The UUID can be taken from e.g. /api/compute_resources/:id/available_virtual_machines, so all the bits are in place. What's lacking is at least the documentation for the uuid parameter in the hosts endpoint. Ideally there could be a more self-descriptive endpoint similar to PUT /api/compute_resources/:id/associate for the import function, which aliases the /api/hosts if that's even possible.</p>	
<p>Where I want to go with this is an ansible module for importing hosts for foreman-ansible-modules.</p>	
<p>Somewhat similar to this https://projects.theforeman.org/issues/27090</p>	
Related issues:	
Related to Foreman - Tracker #27680: API bugs that need workarounds in forema...	New

History

#1 - 11/11/2020 09:23 AM - Anton Nesterov

- Related to Tracker #27680: API bugs that need workarounds in foreman-ansible-modules added