## Foreman - Bug #31348

# Intermediate script is broken due to URL encoded parameters

11/20/2020 06:37 AM - Lukas Zapletal

Status: Closed

Priority: High

Assignee: Lukas Zapletal

Category: Templates

Target version: 2.3.0

**Difficulty:** easy Fixed in Releases: 2.3.0

Triaged: Yes Found in Releases:

Bugzilla link: Red Hat JIRA:

Pull request: https://github.com/theforeman/foreman/pull/8143

### Description

We made a change to cleanup iPXE template code by using <%= foreman\_url('iPXE', mac: "\${net#{i}/mac}") %> which is cleaner but it has one major issue, it renders to URL encoded string:

http://foreman.some.host.fqdn/unattended/iPXE?mac=%24%7Bnet0%2Fmac%7D while this should be http://foreman.some.host.fqdn/unattended/iPXE?mac=\${net0/mac}

This breaks iPXE workflow completely.

### **Associated revisions**

#### Revision 174c7354 - 11/26/2020 12:41 PM - Lukas Zapletal

Fixes #31348 - raw params in foreman\_url support

#### History

## #1 - 11/20/2020 07:39 AM - Lukas Zapletal

- Target version set to 2.3.0
- Triaged changed from No to Yes

Requesting 2.3, this is a regression we introduced which completely breaks iPXE provisioning without tokens.

#### #2 - 11/20/2020 07:40 AM - The Foreman Bot

- Status changed from New to Ready For Testing
- Assignee set to Lukas Zapletal
- Pull request https://github.com/theforeman/foreman/pull/8143 added

## #3 - 11/26/2020 12:41 PM - The Foreman Bot

- Fixed in Releases 2.4.0 added

### #4 - 11/26/2020 12:49 PM - Tomer Brisker

- Fixed in Releases 2.3.0 added
- Fixed in Releases deleted (2.4.0)

### #5 - 11/26/2020 01:01 PM - Lukas Zapletal

- Status changed from Ready For Testing to Closed

Applied in changeset foreman|174c73545fcc4a5d44a695c6904f65c9070cf8f1.

### #6 - 12/01/2020 11:34 AM - Tomer Brisker

- Category set to Templates

05/19/2024 1/1