# Foreman - Bug #315

## Newlines slipping into dynamic partition table layouts

06/07/2010 09:09 PM - Frank Sweetser

Status: Closed
Priority: Normal

Assignee: Ohad Levy

Category: Web Interface

Target version: 0.1-6

Difficulty: Fixed in Releases:
Triaged: Found in Releases:
Bugzilla link: Red Hat JIRA:

Pull request:

### Description

I'm not sure where they slipped in, but custom partition tables are ending up with DOS style line endings. This causes kickstart to fail miserably, since this command:

echo foo > /tmp/diskpart.cfg

ends up becoming:

echo foo > /tmp/diskpart.cfg\r

which creates diskpart.cfg\r instead of diskpart.cfg. I couldn't figure out where in the path they're appearing (web browser, rails, mysql, etc), but I did a simple patch to filter them out of the generated kickstart script.

### **Associated revisions**

## Revision 2a06208d - 06/09/2010 08:05 AM - Ohad Levy

fixes #315 - Newlines slipping into dynamic partition table layouts

### History

### #1 - 06/09/2010 08:18 AM - Ohad Levy

- Status changed from New to Ready For Testing
- % Done changed from 0 to 100

Applied in changeset 2a06208d4b7770329f2cf1f3602e703e5c1cb5f5.

### #2 - 06/09/2010 08:36 AM - Ohad Levy

- Category set to Web Interface
- Status changed from Ready For Testing to Closed
- Assignee set to Ohad Levy
- Target version set to 0.1-6

#### **Files**

0001-Protect-against-r-slipping-into-kickstart-pre-script.patch

785 Bytes

06/07/2010

Frank Sweetser

05/13/2024 1/1