

Foreman - Bug #32075

“Preseed default iPXE” template lacks domain=, causing preseed install to pause

03/11/2021 05:34 PM - Dominique Quatravaux

Status:	Ready For Testing	
Priority:	Normal	
Assignee:		
Category:	Templates	
Target version:		
Difficulty:		Fixed in Releases:
Triaged:	No	Found in Releases: 2.3.2
Bugzilla link:		Red Hat JIRA:
Pull request:	https://github.com/theforeman/foreman/pull/8389	

Description

Unlike e.g. “Discovery Debian kexec,” the “Preseed default iPXE” template lacks a setting for domainname= on the kernel command line. When doing a preseed install, debian-installer will still guess the domain name correctly (either from reverse DNS or from the fact that hostname= is the FDQN, I'm not sure); but it will pause for manual confirmation, thus breaking auto-install flow.

History

#1 - 03/11/2021 05:36 PM - The Foreman Bot

- Status changed from New to Ready For Testing

- Pull request <https://github.com/theforeman/foreman/pull/8389> added

#2 - 03/11/2021 06:18 PM - Dominique Quatravaux

Already fixed in [<https://github.com/theforeman/foreman/commit/2bb8a0edda627c65fe3347091fbd95e86835d244>], nevermind...