

Foreman - Feature #33666

Optionally use ignoredisk in kickstart default partition template

10/08/2021 11:07 PM - Dave Thomas

Status:	Closed	
Priority:	Normal	
Assignee:		
Category:	Templates	
Target version:		
Difficulty:	trivial	Fixed in Releases: 3.1.0
Triaged:	No	Found in Releases: 3.0.0
Bugzilla link:		Red Hat JIRA:
Pull request:	https://github.com/foreman/foreman/pull/8826	
Description		
Similar format to autopart, and only triggered if declared. To avoid all disks being formatted.		
<pre><% if host_param('ignoredisk_options') %> ignoredisk <%= host_param('ignoredisk_options') %> <% end %> zerombr clearpart --all --initlabel autopart <%= host_param('autopart_options') %></pre>		

Associated revisions

Revision 5f5754e6 - 10/20/2021 12:00 PM - Dave Thomas

fixes #33666 - add ignoredisk to kickstart default template

History

#1 - 10/08/2021 11:08 PM - The Foreman Bot

- Status changed from New to Ready For Testing

#2 - 10/20/2021 12:00 PM - The Foreman Bot

- Fixed in Releases 3.1.0 added

#3 - 10/20/2021 01:01 PM - Anonymous

- Status changed from Ready For Testing to Closed

Applied in changeset [foreman|5f5754e67107c871d26b5be68f72a4264a843adc](#).

#4 - 11/15/2021 04:24 PM - Amit Upadhye

- Category set to Templates