

Foreman - Feature #34280

Add `ip_include?` method to IPAM::Base that uses `IPAddr#include?` method

01/18/2022 10:35 AM - Jan Matusz

Status:	Closed	
Priority:	Normal	
Assignee:	Jan Matusz	
Category:	Network	
Target version:		
Difficulty:		Fixed in Releases: 3.2.0
Triaged:	No	Found in Releases:
Bugzilla link:		Red Hat JIRA:
Pull request:	https://github.com/theforeman/foreman/pull/9036	
Description		
Related to: https://github.com/theforeman/foreman_discovery/pull/545		
<p>We need to be able to validate whether user sourced IP set in the form is included in the available subnet. Initially we just ran <code>.include?</code> on a Range object generated through <code>subnet_range</code> method, however, this is extremely inefficient when used on huge subnets (specifically in this case, an IPv6 range inclusion check timed out).</p> <p>This brought <code>IPAddr#include</code> to the spotlight.</p>		

Associated revisions

Revision 337ac271 - 01/18/2022 04:06 PM - Jan Matusz

Fixes #34280 - Add `ip_include?` method to `IPAM::Base`

History

#1 - 01/18/2022 10:37 AM - The Foreman Bot

- Status changed from New to Ready For Testing

- Pull request <https://github.com/theforeman/foreman/pull/9036> added

#2 - 01/18/2022 04:06 PM - The Foreman Bot

- Fixed in Releases 3.2.0 added

#3 - 01/18/2022 05:01 PM - Jan Matusz

- Status changed from Ready For Testing to Closed

Applied in changeset [foreman|337ac271d8a87039bfc709bed0749fdbd9651e7e](https://github.com/foreman/foreman/commit/337ac271d8a87039bfc709bed0749fdbd9651e7e).

#4 - 02/15/2022 01:16 PM - Amit Upadhye

- Category set to Network