Installer - Feature #35496

Add default pulp_deb config during installer runs

09/07/2022 11:22 AM - Quirin Pamp

Status: Closed

Priority: Normal

Assignee: Quirin Pamp

Category: Foreman modules

Target version:

Difficulty: Fixed in Releases: 3.5.0

Triaged: Yes Found in Releases:

Bugzilla link: Red Hat JIRA:

Pull request: https://github.com/theforeman/puppet-pul

pcore/pull/263

Description

Users syncing from partial Ubuntu mirrors (a common scenario) currently get an error.

The solution is to add `FORCE_IGNORE_MISSING_PACKAGE_INDICES = True` to `/etc/pulp/settings.py`.

This should be done by default for all Katello installations with pulp deb.

Associated revisions

Revision 5e2bfd7e - 10/28/2022 10:30 AM - Quirin Pamp

Fixes #35496 - Add default pulp_deb config

https://projects.theforeman.org/issues/35496

For Katello users this is the sane/expected default behaviour. It allows for the synchronization of partial Ubuntu mirrors, a very common use case in the wild. Users often stumble over the error that is thrown for such mirrors without this setting.

History

#1 - 09/07/2022 12:54 PM - The Foreman Bot

- Status changed from New to Ready For Testing
- Pull request https://github.com/theforeman/puppet-pulpcore/pull/263 added

#2 - 10/28/2022 10:30 AM - The Foreman Bot

- Fixed in Releases 3.5.0 added

#3 - 10/28/2022 11:01 AM - Quirin Pamp

- Status changed from Ready For Testing to Closed

 $Applied in changeset \ \underline{puppet-pulpcore} \ \underline{5e2bfd7e335c63998f4abb8d75647cd9837cc2d0}.$

#4 - 11/28/2022 12:23 PM - Ewoud Kohl van Wijngaarden

- Category set to Foreman modules
- Triaged changed from No to Yes

05/22/2024 1/1