

Foreman - Bug #35650

Malformed Debian repository

10/19/2022 03:11 PM - Bernhard Suttner

Status:	Closed	
Priority:	Normal	
Assignee:	Bernhard Suttner	
Category:	Host registration	
Target version:		
Difficulty:		Fixed in Releases: 3.5.0
Triaged:	Yes	Found in Releases:
Bugzilla link:		Red Hat JIRA:
Pull request:	https://github.com/foreman/foreman/pull/9473	

Description

In Host registration -> advanced its possible to enter a debian repository which will then be written to /etc/apt/sources.list.d/foreman_registration.list
Currently, shell_escape is used. If you enter a debian repo like "deb <https://example.com> buster stable" the repo config look like

```
deb\ \ buster\ stable
```

which is unusable.

Associated revisions

Revision [debea6c1](#) - 10/19/2022 04:58 PM - Bernhard Suttner

Fixes #35650 - write correct form of deb repo

In Host registration -> advanced its possible to enter a debian repository which will then be written to /etc/apt/sources.list.d/foreman_registration.list
If you enter a debian repo like "deb <https://example.com> buster stable", shell_escape method would rewrite the string so that it looks like:

```
deb\ \ buster\ stable
```

This repo config can not work. Use save_to_file to write the file.

History

#1 - 10/19/2022 03:18 PM - The Foreman Bot

- Status changed from New to Ready For Testing
- Assignee set to Bernhard Suttner
- Pull request <https://github.com/foreman/foreman/pull/9473> added

#2 - 10/19/2022 04:58 PM - The Foreman Bot

- Fixed in Releases 3.5.0 added

#3 - 10/19/2022 05:01 PM - Bernhard Suttner

- Status changed from Ready For Testing to Closed

Applied in changeset [foreman|debea6c156b9508188e03cab63093bc19f62956](#).

#4 - 11/08/2022 05:34 PM - Ewoud Kohl van Wijngaarden

- Subject changed from Host registration: debian repository malformed to Malformed Debian repository
- Category set to Host registration
- Triaged changed from No to Yes