

Foreman - Bug #36181

pressed netplan provisioning template should treat no subnet consistently with finished template

03/08/2023 02:31 AM - Damon Maria

Status:	Ready For Testing	
Priority:	Normal	
Assignee:		
Category:	Templates	
Target version:		
Difficulty:		Fixed in Releases:
Triaged:	No	Found in Releases:
Bugzilla link:		Red Hat JIRA:
Pull request:	https://github.com/theforeman/foreman/pull/9645	

Description

In the preseed_default_finish.erb template no ipv4 subnet implies dhcp:

```
<% subnet = @host.subnet -%>
<% if @static -%>
  <%- dhcp = false -%>
<% elsif subnet.nil? -%>
  <%- dhcp = true -%>
```

The preseed_netplan_setup.erb template does not:

```
:dhcp => bond.subnet.nil? ? false : bond.subnet.dhcp_boot_mode?
```

This means a host setup with no subnet works everywhere else but creates an invalid netplan.

IMHO no subnet should imply dhcp.

History

#1 - 03/08/2023 02:36 AM - Damon Maria

- Pull request <https://github.com/theforeman/foreman/pull/9645> added

#2 - 03/20/2023 02:34 AM - The Foreman Bot

- Status changed from New to Ready For Testing