Foreman - Bug #36541

inconsistent configuration for Redis as used by Dynflow

06/28/2023 09:30 AM - Evgeni Golov

Status:	Closed		
Priority:	Normal		
Assignee:			
Category:			
Target version:			
Difficulty:		Fixed in Releases:	3.9.0
Triaged:	No	Found in Releases:	3.7.0
Bugzilla link:		Red Hat JIRA:	

Pull request: Description

Ohai,

in https://github.com/theforeman/puppet-foreman/blob/1d09876d7838bcd133add6266f4ba19b936ccb6c/templates/settings.yaml.erb#L9 \(\text{Z} \)

however, the service itself is configured to use localhost/0 in

https://github.com/theforeman/foreman/blob/539373dfa5d85149a9dddb6e73bb378a23e134cb/extras/systemd/dynflow-sidekiq%40.service#L14-L15 as seen during service startup:

Jun 28 09:02:00 katello.example.com dynflow-sidekiq@worker-hosts-queue-1[55989]: 2023-06-28T09:02: 00.648Z pid=55989 tid=17vt INFO: Booting Sidekiq 6.3.1 with redis options {:url=>"redis://localhost:6379/0"}

I have no idea if those two must match, or they are two different/unrelated uses of Redis inside Dynflow. But it seems odd and I would expect to be able to configure it.

Associated revisions

Revision 0d91a7c9 - 10/26/2023 02:42 PM - Eric Helms

Fixes #36541 - Update Redis default databases for dynflow and cache

History

#1 - 10/26/2023 02:22 PM - Eric Helms

- Project changed from Installer to Foreman

#2 - 10/26/2023 02:42 PM - The Foreman Bot

- Fixed in Releases 3.9.0 added

#3 - 10/26/2023 03:00 PM - Eric Helms

- Status changed from New to Closed

Applied in changeset foreman | 0d91a7c91cdf5551b5ddc124455c1641afb7c225.

06/02/2024 1/1