

Foreman - Bug #36847

Wrong initrd extension for preseed_default_ipxe

10/20/2023 09:30 AM - Artur Obolewicz

Status:	Ready For Testing	
Priority:	Normal	
Assignee:	Ewoud Kohl van Wijngaarden	
Category:		
Target version:		
Difficulty:		Fixed in Releases: 3.7.1
Triaged:	No	Found in Releases: 3.7.0
Bugzilla link:		Red Hat JIRA:
Pull request:	https://github.com/theforeman/foreman/pull/9870 , https://github.com/theforeman/foreman/pull/10156	

Description

In the current preseed_default_ipxe.erb template:

```
initrd=initrd.img
```

but in official Debian repositories

<http://ftp.debian.org/debian/dists/bullseye/main/installer-amd64/current/images/netboot/debian-installer/amd64/initrd.gz>

```
initrd=initrd.gz
```

It is causing an issue with preseed_default_ipxe template which has hardcoded wrong name.

Solution is to change the name to `initrd.gz`

History

#1 - 10/20/2023 09:45 AM - The Foreman Bot

- Status changed from New to Ready For Testing

- Pull request <https://github.com/theforeman/foreman/pull/9870> added

#2 - 05/10/2024 01:17 PM - The Foreman Bot

- Assignee set to Ewoud Kohl van Wijngaarden

- Pull request <https://github.com/theforeman/foreman/pull/10156> added