

Katello - Bug #37151

hammer allows creation of content overrides other than 'enabled'

02/07/2024 06:00 PM - Jeremy Lenz

Status:	New	
Priority:	Normal	
Assignee:		
Category:	Subscriptions	
Target version:	Katello 4.13.0	
Difficulty:		Fixed in Releases:
Triaged:	Yes	Found in Releases:
Bugzilla link:		Red Hat JIRA:
Pull request:		

Description

In Candlepin, content overrides are attached to a consumer (content host) and have 'name' and a 'value' attributes:

```
hammer activation-key content-override [OPTIONS]
```

```
--override-name VALUE      Override parameter key or name.
```

To enable or disable a repo select 'enabled'.

Default value: enabled

Default: "enabled"

```
--value VALUE              Override value. Note for repo enablement you can use a boolean value
```

In the web UI, the only content overrides displayed are those with the name 'enabled.' However, you can use subscription-manager to set other overrides on the host. For example:

```
subscription-manager repo-override --add gpgcheck:0 --repo satellite-client-6-for-rhel-8-x86_64-rpms
```

This will cause your redhat.repo file to be altered to say

```
gpgcheck = 0
```

In Katello, we do not support or display any overrides besides 'enabled'. However, they can be added via hammer. As these are unsupported, we should disallow this in Hammer as well.

needs removal from both

```
hammer host subscription content-override
```

```
hammer activation-key content-override
```

History

#1 - 02/07/2024 06:41 PM - Chris Roberts

- Target version set to Katello 4.13.0

- Triaged changed from No to Yes