# Installer - Bug #37308

## Fix apache config so REMOTE\_USER is not unset for pulpcore registry

03/28/2024 04:54 PM - Ian Ballou

Status: Closed

Priority: Normal

Assignee: Ian Ballou

Category: Foreman modules

Target version: 3.11.0

Triaged: No Found in Releases:

Bugzilla link: Red Hat JIRA: SAT-24245

Pull request: https://github.com/theforeman/puppet-pul

pcore/pull/337

### Description

Difficulty:

Any calls to /pulpcore\_registry/v2/ lose REMOTE\_USER in the headers. This header is necessary to authenticate with Pulp to push container content.

Fixed in Releases:

3.11.0

To work around it, I removed every reference to setting / unsetting REMOTE\_USER in /etc/httpd/conf.d/05-foreman-ssl.conf and added `RequestHeader set REMOTE\_USER "admin"`. Only then did the REMOTE\_USER header get sent to Pulp.

#### **Associated revisions**

#### Revision 21aa39e2 - 04/11/2024 01:19 PM - Ian Ballou

Fixes #37308 - set REMOTE\_USER properly for pulpcore registry

### History

### #1 - 03/28/2024 05:51 PM - The Foreman Bot

- Status changed from New to Ready For Testing
- Assignee set to Ian Ballou
- Pull request https://github.com/theforeman/puppet-pulpcore/pull/337 added

### #2 - 04/11/2024 01:19 PM - The Foreman Bot

- Fixed in Releases 3.11.0 added

## #3 - 04/11/2024 02:00 PM - Anonymous

- Status changed from Ready For Testing to Closed

 $Applied \ in \ changeset \ \underline{puppet-pulpcore} \ \underline{[21aa39e28f19b40bf328ebba514465fb9cfb9fe2]}.$ 

05/04/2024 1/1