

Foreman - Bug #37353

always use cached manifest json to find webpack chunks, not only for JS

04/15/2024 10:30 AM - Evgeni Golov

<b>Status:</b>	Closed	
<b>Priority:</b>	Normal	
<b>Assignee:</b>	Evgeni Golov	
<b>Category:</b>	JavaScript stack	
<b>Target version:</b>		
<b>Difficulty:</b>		<b>Fixed in Releases:</b> 3.11.0
<b>Triaged:</b>	No	<b>Found in Releases:</b>
<b>Bugzilla link:</b>		<b>Red Hat JIRA:</b>
<b>Pull request:</b>	https://github.com/foreman/foreman/pull/10127	
<b>Description</b>		
In <a href="#">#37102</a> a cache was used to speed up loading webpack chunks, but only JS code uses the cache		
<b>Related issues:</b>		
Related to Foreman - Refactor #37102: Update to webpack 5		Closed

Associated revisions

Revision 6924b150 - 04/15/2024 11:09 AM - Evgeni Golov

Fixes #37353 - always read cached webpack manifest

History

#1 - 04/15/2024 10:32 AM - The Foreman Bot

- Status changed from New to Ready For Testing
- Pull request <https://github.com/foreman/foreman/pull/10127> added

#2 - 04/15/2024 10:41 AM - Evgeni Golov

- Related to Refactor #37102: Update to webpack 5 added

#3 - 04/15/2024 11:10 AM - The Foreman Bot

- Fixed in Releases 3.11.0 added

#4 - 04/15/2024 12:00 PM - Evgeni Golov

- Status changed from Ready For Testing to Closed

Applied in changeset [foreman|6924b150a194709bb71fede89768f485173b85d6](#).