

Foreman - Bug #37353

always use cached manifest json to find webpack chunks, not only for JS

04/15/2024 10:30 AM - Evgeni Golov

Status:	Closed	
Priority:	Normal	
Assignee:	Evgeni Golov	
Category:	JavaScript stack	
Target version:		
Difficulty:		Fixed in Releases: 3.11.0
Triaged:	No	Found in Releases:
Bugzilla link:		Red Hat JIRA:
Pull request:	https://github.com/foreman/foreman/pull/10127	
Description		
In #37102 a cache was used to speed up loading webpack chunks, but only JS code uses the cache		
Related issues:		
Related to Foreman - Refactor #37102: Update to webpack 5		Closed

Associated revisions

Revision 6924b150 - 04/15/2024 11:09 AM - Evgeni Golov

Fixes #37353 - always read cached webpack manifest

History

#1 - 04/15/2024 10:32 AM - The Foreman Bot

- Status changed from New to Ready For Testing

- Pull request <https://github.com/foreman/foreman/pull/10127> added

#2 - 04/15/2024 10:41 AM - Evgeni Golov

- Related to Refactor #37102: Update to webpack 5 added

#3 - 04/15/2024 11:10 AM - The Foreman Bot

- Fixed in Releases 3.11.0 added

#4 - 04/15/2024 12:00 PM - Evgeni Golov

- Status changed from Ready For Testing to Closed

Applied in changeset [foreman|6924b150a194709bb71fede89768f485173b85d6](#).