Foreman - Bug #3923

organzation relations not documented through apipie

12/20/2013 03:00 PM - Thomas McKay

Status:	Closed		
Priority:	Normal		
Assignee:			
Category:	API		
Target version:			
Difficulty:		**Fixed in Releases:**	
Triaged:	No	**Found in Releases:**	
Bugzilla link:		**Red Hat JIRA:**	
Pull request:			

Description

Where are the relations documented if not here? I cannot find the apipie docs to match the hammer organization add_ and remove_ subcommands.

```
$ bundle exec hammer -v organization --help
Usage:
hammer organization [OPTIONS] SUBCOMMAND [ARG] ...

Parameters:
SUBCOMMAND                subcommand
[ARG] ...                 subcommand arguments

Subcommands:
list                List all organizations
info                Show an organization
create              Create an organization
update              Update an organization
delete              Delete an organization
add_configtemplate       Associate a resource
remove_configtemplate        Disassociate a resource
add_user            Associate a resource
remove_user             Disassociate a resource
add_smartproxy          Associate a resource
remove_smartproxy        Disassociate a resource
add_computeresource       Associate a resource
remove_computeresource      Disassociate a resource
add_subnet          Associate a resource
remove_subnet           Disassociate a resource
add_medium          Associate a resource
remove_medium            Disassociate a resource
add_domain          Associate a resource
remove_domain            Disassociate a resource
add_environment          Associate a resource
remove_environment        Disassociate a resource
add_hostgroup           Associate a resource
remove_hostgroup         Disassociate a resource

Options:
-h, --help          print help
```

History

#1 - 04/21/2021 11:47 AM - Leos Stejskal

- Status changed from New to Closed

Documentation for the add|remove commands is available in help, like this:

```
hammer organization  add-hostgroup -h
Usage:
    hammer organization add-hostgroup [OPTIONS]

Options:
 --hostgroup[-id|-title]         Set the current hostgroup context for the request. Name/Title/Id can be use
d
 --id ID
 --name NAME                     Set the current organization context for the request
 --title TITLE                   Set the current organization context for the request
 -h, --help                      Print help
```

Closing the issue

```
hammer organization  add-hostgroup -h
Usage:
    hammer organization add-hostgroup [OPTIONS]

Options:
 --hostgroup[-id|-title]         Set the current hostgroup context for the request. Name/Title/Id can be use
d
 --id ID
 --name NAME                     Set the current organization context for the request
 --title TITLE                   Set the current organization context for the request
 -h, --help                      Print help
```