

Foreman - Feature #3926

have more control over the DHCP Option being used.

12/23/2013 01:15 PM - Jelle B.

<div>Status:Rejected</div> <div>Priority:Low</div> <div>Assignee:</div> <div>Category:</div> <div>Target version:</div> <div>Difficulty:</div> <div>Triaged:</div> <div>Bugzilla link:</div> <div>Pull request:</div>	<div>Fixed in Releases:</div> <div>Found in Releases:</div> <div>Red Hat JIRA:</div>
<div>Description</div> <div>I have run into the issue that the dhcpd.conf options do not reflect what foreman is setting when it adds a hosts on ISC DHCPD on Debian 7.3.</div> <div>In the DHCPD.conf I have :</div> <div><div>1. PXE Handoff.</div><div>next-server 10.26.26.51;</div><div>filename "tftpboot/pxelinux.0";</div></div> <div>But forman pushes :</div> <div>omshell: executed - set statements = "filename = \"pxelinux.0\"; next-server = 0a:1a:1a:33; option host-name = \"lab-dhcpdns-test.lab....&lt;snip&gt;</div> <div>This is without the extar folder and as such the host wont boot, the reason I have folders on my tftp is simepl it is a shared NFS share mounted into various locations and also has folders for firewall , router and switch images/configs and the folders keep it organised. But alo this enables me to not have multiple locations with the same boot images etc.</div> <div>Thanks.</div> <div>I would like to see some more control over these options either via the settings interface or maybe on a foreman-proxy config level already.</div>	

History

#1 - 05/18/2017 07:09 PM - Anonymous

- Status changed from New to Rejected

works as designed.