

Foreman - Bug #4008

Disable 'build mode' unsuccessful

01/14/2014 07:43 AM - Thomas Linck

| | |
|---|------------------------------|
| Status: Duplicate | |
| Priority: Normal | |
| Assignee: | |
| Category: Templates | |
| Target version: | |
| Difficulty: | Fixed in Releases: |
| Triaged: | Found in Releases: |
| Bugzilla link: | Red Hat JIRA: |
| Pull request: | |
| Description | |
| <p>We have a foreman instance running with puppet on a debian host with following versions:</p> <p>Foreman from packages Version : 1.3.1-1</p> <p>Puppet from packages Version : 2.7.23-1~deb7u1</p> <p>We had to change some items name for functional purpose. We updated name of hostgroup, templates, classes ... Since this name update we are not able to disable 'build mode' on all hosts. Gui returns an error message like 'Failed to cancel pending build for <hostname>'. In error log this message is related to the following extract:</p> <pre>Started GET "/hosts/<hostname>.localdomain/cancelBuild" for <myIpAddr> at 2014-01-14 07:30:41 +000 0 Processing by HostsController#cancelBuild as HTML Parameters: {"id"=>"<hostname>.localdomain"} Add the TFTP configuration for <hostname>.localdomain Failed to generate PXELinux template: undefined method `template' for nil:NilClass Delete the autosegn entry for <hostname>.localdomain Rolling back due to a problem: [] Adding autosegn entry for <hostname>.localdomain Delete the TFTP configuration for <hostname>.localdomain Failed to save: Failed to generate PXELinux template: undefined method `template' for nil:NilClass Redirected to https://foreman/hosts/<hostname>.localdomain Completed 302 Found in 702.1ms (ActiveRecord: 17.2ms)</pre> <p>As we gave Foreman an important role in our production system, this issue is really relevant to us and is not compatible with production system. Please check this issue as soon as possible as it really matters to us. For any further informations, let me know.</p> | |
| Related issues: | |
| Is duplicate of Foreman - Bug #2792: If you delete "PXE Localboot Default" ca... | New 07/15/2013 |

History

#1 - 01/14/2014 08:22 AM - Dominic Cleal

- translation missing: en.field_release deleted (1)

#2 - 01/14/2014 08:27 AM - Dominic Cleal

- Is duplicate of Bug #2792: If you delete "PXE Localboot Default" cancel build fails added

#3 - 01/14/2014 08:28 AM - Dominic Cleal

- Status changed from New to Feedback

This error suggests to me the PXELinux localboot template can't be resolved for the host. The name of these is important as Foreman searches for

them in order to rewrite the menu on the TFTP server, but it will let you rename them, even though you shouldn't.

Please rename the localboot template(s) back to the original name and that should resolve the issue.

#4 - 01/14/2014 08:44 AM - Thomas Linck

Thank you Dominic for your help.

I think I never had this template, the one used for built host (localboot) seems to be named : "PXE Default File".

It's the only template I have remaining from default installation I think.

This template was not anymore of 'Kind' 'PXELinux' so I set it back to 'PXELinux'(empty before), didn't solve the issue.

Should I add "the PXELinux localboot template"? I mean, with this exact name? Rename "PXE Default File" to "PXELinux localboot" ?

#5 - 01/14/2014 08:48 AM - Dominic Cleal

The PXE default file is used as the global default, not for local booting when build mode is disabled, so leave that one along.

You can copy the one here and add it with the name "PXE Localboot Default":

https://github.com/theforeman/community-templates/blob/master/pxe/PXELinux_local.erb

#6 - 01/14/2014 09:25 AM - Thomas Linck

Perfectly solved the issue.

I can't update issue status but for me it can be closed.

Thank's again.

#7 - 01/14/2014 10:13 AM - Dominic Cleal

- *Status changed from Feedback to Duplicate*

Good to hear, thanks.