

## Foreman - Feature #438

### automatically associate the host domain

11/07/2010 11:50 AM - Ohad Levy

<b>Status:</b> Closed	
<b>Priority:</b> Normal	
<b>Assignee:</b> Ohad Levy	
<b>Category:</b> Host creation	
<b>Target version:</b> 0.1-6	
<b>Difficulty:</b>	<b>Fixed in Releases:</b>
<b>Triaged:</b>	<b>Found in Releases:</b>
<b>Bugzilla link:</b>	<b>Red Hat JIRA:</b>
<b>Pull request:</b>	
<b>Description</b> as of <a href="#">#398</a> , domain names were not automatically created, nor assigned to an host. while creating domain names might lead to problems (See <a href="#">#398</a> ), it should be possible to associate the domain if it already exists.	

#### Associated revisions

##### Revision 3af5f2e6 - 11/08/2010 12:31 PM - Ohad Levy

fixes #438 - automatically associate the host domain

This reverts a behaviour prior to #398, the main difference is that the domain will not be created, rather only existing will be used.

#### History

##### #1 - 11/08/2010 12:33 PM - Ohad Levy

- Status changed from New to Ready For Testing
- % Done changed from 0 to 100

Applied in changeset [3af5f2e6304638eab712c232d7ede1b8e7971d0d](#).

##### #2 - 11/08/2010 12:33 PM - Ohad Levy

- Status changed from Ready For Testing to Closed