

Foreman - Feature #470

Add kickstart via gpXE support

11/16/2010 12:46 PM - Ohad Levy

Status: Closed	
Priority: Normal	
Assignee: Ohad Levy	
Category: Unattended installations	
Target version: 0.2	
Difficulty:	Fixed in Releases:
Triaged:	Found in Releases:
Bugzilla link:	Red Hat JIRA:
Pull request:	
Description	
This will allow alternative methods of provisioning hosts (it would be possible to skip tftp altogether).	
Related issues:	
Related to Foreman - Bug #4020: @static only works in kickstart templates	Closed 01/15/2014

Associated revisions

Revision 14dd0353 - 11/16/2010 01:00 PM - Ohad Levy

fixes #470 - Add gpXE scripts support

This commit implements the following:

- dynamic gpXE script that kickstart purely with gpXE - see usage example below
- add static network option to kickstart, ie if added ?static=true to the url, network configuration would be static at the moment this should only be used with gpXE, or alternatively you would need to provide the network information as a kernel argument (see gpXE_kickstart_config file as an example for that).

gpXE usage example

```
press ctrl-b for interactive mode
#get network from dhcp
dhcp net0
#or set static
ifopen
set net0/ip <your host ip>
set net0/netmask <netmask>
set net0/gateway <your gateway>
set net0/dns <dns server>
```

1. tell gpXE to ask foreman for instructions
kernel http://foreman/unattended/gpXE_kickstart_config
boot

Revision 552638db - 11/16/2010 08:29 PM - Ohad Levy

fixes typo - refs #470

History

#1 - 11/16/2010 01:01 PM - Ohad Levy

- Status changed from New to Ready For Testing

- % Done changed from 0 to 100

Applied in changeset [14dd0353b2c7d16084a13c7b1ab52630887cabe3](#).

#2 - 11/16/2010 01:03 PM - Ohad Levy

- Subject changed from Add gpXE scripts support to Add kickstart via gpXE support

#3 - 11/17/2010 11:53 AM - Ohad Levy

- Status changed from Ready For Testing to Closed

#4 - 04/25/2019 12:47 PM - Lukas Zapletal

- Related to Bug #4020: @static only works in kickstart templates added