

Foreman - Bug #4977

setting root_pass to empty string from the settings page breaks foreman

03/31/2014 03:58 PM - cristian falcas

Status:	Resolved	Fixed in Releases: Found in Releases: Red Hat JIRA:
Priority:	Normal	
Assignee:		
Category:	Settings	
Target version:		
Difficulty:		
Triaged:		
Bugzilla link:		
Pull request:		
Description		
After I set the root_pass parameter to an empty string, I couldn't edit host_group on any host.		
I put foreman in debug mode, but there was no relevant output.		
Also, as a side note, i found it unintuitive to have root_pass in foreman and the exported name to be root_pw in puppet.		
Version of foreman is 1.4.1		
Related issues:		
Related to Foreman - Feature #3725: Make default root password more explicit ...		Closed 11/22/2013

History

#1 - 03/31/2014 04:02 PM - Dominic Cleal

- Category set to Settings
- Status changed from New to Feedback

Would you be able to re-test on Foreman 1.5? The default has now changed to an empty string, so I think it should now work.

#2 - 03/31/2014 04:04 PM - cristian falcas

Sure, I will update and retest when foreman 1.5 will be available.

#3 - 03/31/2014 04:07 PM - Dominic Cleal

- Related to Feature #3725: Make default root password more explicit and configurable at install time added

#4 - 04/30/2014 07:14 AM - cristian falcas

This is fixed in 1.5

Thank you

#5 - 04/30/2014 07:46 AM - Dominic Cleal

- Status changed from Feedback to Resolved

Thanks!