

## Foreman - Feature #5175

### Possibility to run puppet agent with --noop flag from foreman UI

04/14/2014 08:28 AM - Petter Hassberg

<b>Status:</b> Closed	
<b>Priority:</b> Normal	
<b>Assignee:</b>	
<b>Category:</b> Puppet integration	
<b>Target version:</b>	
<b>Difficulty:</b>	<b>Fixed in Releases:</b>
<b>Triaged:</b> No	<b>Found in Releases:</b>
<b>Bugzilla link:</b>	<b>Red Hat JIRA:</b>
<b>Pull request:</b>	
<b>Description</b> Sometimes you want to run a puppet agent with noop flag if you've introduced a lot of changes, just to see what would've happened from the generated report.	
<b>Related issues:</b> Related to Foreman - Feature #1373: Support puppet kick (puppetrun) options <b>New</b> 12/06/2011	

#### History

##### #1 - 04/15/2014 02:15 PM - Dominic Cleal

- Tracker changed from Bug to Feature

##### #2 - 01/04/2016 04:11 AM - julien ippolito

Hi,

I have the opposite case :

All my node run puppet as a service with the noop attribute.

I want when i use puppetrun tu specify if the node need to run with the tag noop or no-noop

##### #3 - 03/17/2016 04:44 AM - Dominic Cleal

- Related to Feature #1373: Support puppet kick (puppetrun) options added

##### #4 - 09/14/2020 07:45 AM - Marek Hulán

- Status changed from New to Closed

This is implemented via REX I believe, obsolete puppet run was removed from Foreman. I'm closing this request, please reopen if I missed something.