

## Smart Proxy - Bug #5435

### HTTP 406 Error on Environment or Module Import from Puppet Master

04/24/2014 07:41 PM - Zach Crownover

<b>Status:</b>	Duplicate	
<b>Priority:</b>	High	
<b>Assignee:</b>		
<b>Category:</b>	Puppet	
<b>Target version:</b>		
<b>Difficulty:</b>		<b>Fixed in Releases:</b>
<b>Triaged:</b>		<b>Found in Releases:</b> 1.3.2
<b>Bugzilla link:</b>		<b>Red Hat JIRA:</b>
<b>Pull request:</b>		

#### Description

Backstory,

I had modules I downloaded from the forge and had them named as their tarballs were in the /etc/puppet/development/modules, initially things like puppetlabs-stdlib-versionsomething, I did a git mv to make them just stdlib and so on, after the puppet master did a git pull, it was no longer able to import environments or modules/classes. Most of the services appear to still be running, it's still reporting and acting as an ENC for what's there, but I can't update modules/classes/environments, or bring in anything new. If I go to Configuration->Environments and click on import from puppet-master-1 then I get the HTTP 406 error. I also get it if I go to Configuration->Puppet Classes and click on import from puppet-master-1.

This is the output from the class section.

Oops, we're sorry but something went wrong

x 406 Not Acceptable

If you feel this is an error with Foreman itself, please open a new issue with Foreman ticketing system, You would probably need to attach the Full trace and relevant log entries.

```
RestClient::NotAcceptable
```

```
406 Not Acceptable
```

```
lib/proxy_api/resource.rb:68:in `get'
```

```
lib/proxy_api/puppet.rb:9:in `environments'
```

```
app/services/puppet_class_importer.rb:121:in `actual_environments'
```

```
app/services/puppet_class_importer.rb:21:in `changes'
```

```
app/controllers/concerns/foreman/controller/environments.rb:10:in `import_environments'
```

```
app/models/concerns/foreman/thread_session.rb:33:in `clear_thread'
```

This is the output from the environment section

Oops, we're sorry but something went wrong

x 406 Not Acceptable

If you feel this is an error with Foreman itself, please open a new issue with Foreman ticketing system, You would probably need to attach the Full trace and relevant log entries.

```
RestClient::NotAcceptable
```

```
406 Not Acceptable
```

```
lib/proxy_api/resource.rb:68:in `get'
```

```
lib/proxy_api/puppet.rb:9:in `environments'
```

```
app/services/puppet_class_importer.rb:121:in `actual_environments'
```

```
app/services/puppet_class_importer.rb:21:in `changes'
```

```
app/controllers/concerns/foreman/controller/environments.rb:10:in `import_environments'
```

```
app/models/concerns/foreman/thread_session.rb:33:in `clear_thread'
```

#### History

#1 - 04/25/2014 07:41 AM - Dominic Cleal

- Project changed from Foreman to Smart Proxy

- Category set to Puppet

The error is coming from the proxy service, so check /var/log/foreman-proxy/proxy.log for more information. It should show the error in its logs.

## #2 - 04/25/2014 07:42 AM - Dominic Cleal

- Status changed from New to Need more information

## #3 - 04/25/2014 07:11 PM - Zach Crowover

This is what shows up in /var/log/foreman-proxy/proxy.log

```
I, [2014-04-25T19:08:14.330708 #16257] INFO -- : Initializing from Puppet config file: /etc/puppet/puppet.conf
E, [2014-04-25T19:08:14.350135 #16257] ERROR -- : Failed to list puppet environments: undefined method `[]' for nil:NilClass
```

Also, this is a VMware VM, with 4GB RAM running CentOS 6.5 with 1 [CPU@2.4Ghz](#).

This is the contents of my /etc/puppet/puppet.conf with the domain removed for privacy reasons.

```
#####
```

1. This file is managed by Puppet, any changes to it will be overwritten at ###
2. next system check-in. If changes need to be made, please consult your ###
3. local sysadmin for them to be done. ###

```
#####
```

```
[main] # The Puppet log directory. # The default value is '$vardir/log'.
```

```
logdir = /var/log/puppet
```

1. Where Puppet PID files are kept.
2. The default value is '\$vardir/run'.

```
rundir = /var/run/puppet
```

1. Where SSL certificates are kept.
2. The default value is '\$confdir/ssl'.

```
ssldir = $vardir/ssl
```

1. Allow services in the 'puppet' group to access key (Foreman + proxy)

```
privatekeydir = $ssldir/private_keys { group = service }
hostprivkey = $privatekeydir/$certname.pem { mode = 640 }
```

1. Puppet 3.0.x requires this in both [main] and [master] - harmless on agents

```
autosign = $confdir/autosign.conf { mode = 664 }
```

```
pluginsync = true
```

```
[agent] # The file in which puppetd stores a list of the classes # associated with the retrieved configuration. Can be loaded in # the separate
`puppet` executable using the `--loadclasses` # option. # The default value is '$confdir/classes.txt'.
```

```
classfile = $vardir/classes.txt
```

1. Where puppetd caches the local configuration. An
2. extension indicating the cache format is added automatically.
3. The default value is '\$confdir/localconfig'.

```
localconfig = $vardir/localconfig
```

1. Disable the default schedules as they cause continual skipped

2. resources to be displayed in Foreman - only for Puppet >= 3.4

```
default_schedules = false
```

```
report = true
pluginsync = true
masterport = 8140
environment = production
certname = puppet-master-1.example.com
server = puppet-master-1.example.com
listen = false
splay = false
runinterval = 1800
noop = false
show_diff = false
configtimeout = 120
```

```
[master]
```

```
autosign    = $conffdir/autosign.conf { mode = 664 }
reports     = foreman
external_nodes = /etc/puppet/node.rb
node_terminus = exec
ca          = true
ssldir     = /var/lib/puppet/ssl
```

[development]

```
modulepath  = /etc/puppet/environments/development/modules:/etc/puppet/environments/common:/usr/share/puppet/modules
config_version =
```

[production]

```
modulepath  = /etc/puppet/environments/production/modules:/etc/puppet/environments/common:/usr/share/puppet/modules
config_version =
```

Please let me know if you need other information.

#### #4 - 04/25/2014 07:13 PM - Zach Crowover

I'm sorry, I should've used the pre tag.

```
#####
### This file is managed by Puppet, any changes to it will be overwritten at ###
### next system check-in. If changes need to be made, please consult your   ###
### local sysadmin for them to be done.                                     ###
#####
```

[main]

```
# The Puppet log directory.
# The default value is '$vardir/log'.
logdir = /var/log/puppet
```

```
# Where Puppet PID files are kept.
# The default value is '$vardir/run'.
rundir = /var/run/puppet
```

```
# Where SSL certificates are kept.
# The default value is '$conffdir/ssl'.
ssldir = $vardir/ssl
```

```
# Allow services in the 'puppet' group to access key (Foreman + proxy)
privatekeydir = $ssldir/private_keys { group = service }
hostprivkey = $privatekeydir/$certname.pem { mode = 640 }
```

```
# Puppet 3.0.x requires this in both [main] and [master] - harmless on agents
autosign      = $conffdir/autosign.conf { mode = 664 }
```

```
pluginsync = true
```

[agent]

```
# The file in which puppetd stores a list of the classes
# associated with the retrieved configuration. Can be loaded in
# the separate ``puppet`` executable using the ``--loadclasses``
# option.
# The default value is '$conffdir/classes.txt'.
classfile = $vardir/classes.txt
```

```
# Where puppetd caches the local configuration. An
# extension indicating the cache format is added automatically.
# The default value is '$conffdir/localconfig'.
localconfig = $vardir/localconfig
```

```
# Disable the default schedules as they cause continual skipped
# resources to be displayed in Foreman - only for Puppet >= 3.4
default_schedules = false
```

```
report      = true
pluginsync  = true
masterport  = 8140
environment = production
certname    = puppet-master-1.example.com
server      = puppet-master-1.example.com
listen      = false
splay       = false
runinterval = 1800
noop        = false
```

```
show_diff      = false
configtimeout  = 120
```

[master]

```
autosign       = $confdir/autosign.conf { mode = 664 }
reports        = foreman
external_nodes = /etc/puppet/node.rb
node_terminus  = exec
ca             = true
ssldir         = /var/lib/puppet/ssl
```

[development]

```
modulepath     = /etc/puppet/environments/development/modules:/etc/puppet/environments/common:/usr/share/puppet/modules
config_version =
```

[production]

```
modulepath     = /etc/puppet/environments/production/modules:/etc/puppet/environments/common:/usr/share/puppet/modules
config_version =
```

#### #5 - 04/28/2014 07:42 AM - Dominic Cleal

Which version of Puppet is installed?

#### #6 - 04/28/2014 08:23 PM - Zach Crownover

```
$ facter -p
architecture => x86_64
augeasversion => 1.0.0
blockdevice_sda_model => Virtual disk
blockdevice_sda_size => 32212254720
blockdevice_sda_vendor => VMware
blockdevice_sdb_model => Virtual disk
blockdevice_sdb_size => 32212254720
blockdevice_sdb_vendor => VMware
blockdevice_sr0_model => VMware IDE CDR10
blockdevice_sr0_size => 1073741312
blockdevice_sr0_vendor => NECVMWar
blockdevices => sda,sdb,sr0
domain => aristanetworks.com
facterversion => 2.0.1
filesystems => ext4,iso9660
fqdn => puppet-master-1.example.com
hardwareisa => x86_64
hardwaremodel => x86_64
hostname => puppet-master-1
id => zcrownover
interfaces => eth0,lo,virbr0,virbr0_nic
ipaddress => 172.22.22.231
ipaddress6 => fd7a:629f:52a4:1616:250:56ff:fe95:72d2
ipaddress_eth0 => 172.22.22.231
ipaddress_lo => 127.0.0.1
ipaddress_virbr0 => 192.168.122.1
is_virtual => true
kernel => Linux
kernelmajversion => 2.6
kernelrelease => 2.6.32-431.11.2.el6.x86_64
kernelversion => 2.6.32
macaddress => 00:50:56:95:72:D2
macaddress_eth0 => 00:50:56:95:72:D2
macaddress_virbr0 => 52:54:00:19:8F:D9
macaddress_virbr0_nic => 52:54:00:19:8F:D9
memoryfree => 1.40 GB
memoryfree_mb => 1438.21
memorysize => 3.74 GB
memorysize_mb => 3832.86
mtu_eth0 => 1500
mtu_lo => 16436
mtu_virbr0 => 1500
mtu_virbr0_nic => 1500
netmask => 255.255.255.0
netmask_eth0 => 255.255.255.0
netmask_lo => 255.0.0.0
netmask_virbr0 => 255.255.255.0
network_eth0 => 172.22.22.0
```

```
network_lo => 127.0.0.0
network_virbr0 => 192.168.122.0
operatingsystem => CentOS
operatingsystemmajrelease => 6
operatingsystemrelease => 6.5
osfamily => RedHat
path => /usr/local/bin:/bin:/usr/bin:/usr/local/sbin:/usr/sbin:/sbin:/home/zcrownover/bin
physicalprocessorcount => 1
processor0 => Intel(R) Xeon(R) CPU      E5620 @ 2.40GHz
processorcount => 1
ps => ps -ef
puppetversion => 3.5.1
rubysitedir => /usr/lib/ruby/site_ruby/1.8
rubyversion => 1.8.7
selinux => true
selinux_config_mode => enforcing
selinux_config_policy => targeted
selinux_current_mode => enforcing
selinux_enforced => true
selinux_policyversion => 24
sshdsakey =>
AAAAB3NzaC1kc3MAAACBAI5pjlwp8/+OEHmFhEbcJLQ+iFcRsH2bgeKRk+JLQo5Txlur4bJVSE+6ve66Gtm1vQ4D2ee5USxHznCPsbODFykWPbm
qoyB/VG44wXe7KJi2v2EQX1Z2nDmE4Gk8DtcTmAZ+GJqkdO0uuXAfPMU88pslcHexzKrGowxKqBc651AAAFQCSp/Cs2yIRO9UgtmUlauSSDG8p
1wAAAIbJi1ydfA0Is/4XViO3EI8H+BZkvCGE1Buwbdx7Haaztx534/1mrzmUOLN5R3aQxZeajFcTdXpOgNIYghlNUXM6e6CG6SV/ZGbWvf/M4uUvbTM
6Yc9T4YIKzjHpd57aecxDOaiKp+W4i8Fs1hKAHBIWg3oJFq02c8XO1BDsRcTHPwAAAIb/HHnSaCZ4TciO2fDUVHixU1oQzF2G/mlvVE1fzPLngJ/Blc
xySqy+5ebojfnJfMkE6dlj1cfl0Gyv20TMFg5U+G2mqjEwErzPrJB7tNXtP1gqXi6gpoh1sNmCLvaC9pJRf08KgGoB0dmDFKpH6hv8mmrRdVV38mOk+
Q+Watb7Q==
sshfdsa => SSHFP 2 1 a1f362eacbee56c260fe8866ca24cb06c4bf45f9
SSHFP 2 2 0135175012e7119c757b8df5ad8f11ea5c41debaa56b6903a86d4d7d1f458273
sshfdsa => SSHFP 1 1 85d9f93f250a169d2f76b64217eb89a228ce9161
SSHFP 1 2 ef0492e076207ec29fdded836ada1822943918b8c8eacfd1c5e22927daf2d98d
sshdsakey =>
AAAAB3NzaC1yc2EAAAABlwAAAEAAzQel5xmEk8HL7+YY3Q2mR15Zs7+WUqLpznzTSEp4PVz0VCLKon3nVTZQldg301KI7RtN0bua1x1Ax0pzKR
WO/i1IfxsK0JVlleUEjk7w2ySvz/kbhtZREtaFA89LxX2tHph9OxgBaD+RXKJ4IK3oSRuh4xxXcgqBa/KgzEcSnH9xCXN/nXPVyoEeirzF6HKe8bmjdlzPO
ayWNC5TDlrUikzMgJSQzFvT/bql7ezpQq/e9YTdoW3FuWJ69vdtHCYUf1/1WP2+dMrg0PllghAWMeedqLlnhFziL3ZCmbmsmYixDJ1vjgM58TOHKt8Obi
oCgDths7bVHfieaPkwQVACyw==
swapfree => 3.87 GB
swapfree_mb => 3967.99
swapsize => 3.87 GB
swapsize_mb => 3967.99
timezone => UTC
uniqueid => 16ace716
uptime => 5 days
uptime_days => 5
uptime_hours => 139
uptime_seconds => 501828
virtual => vmware
```

#### #7 - 04/29/2014 07:31 AM - Dominic Cleal

- Status changed from Need more information to Duplicate

Ah okay, this is an incompatibility between Smart Proxy 1.3.x and Puppet 3.5.1, see bug [#4658](#). For 3.5.1 compatibility, you'll need to use Smart Proxy 1.4.2 or higher. This would be compatible with Foreman 1.3.x if you only want to upgrade this component.

<http://theforeman.org/manuals/1.4/index.html#3.1.2PuppetCompatibility> has more compatibility information.