# Foreman - Bug #5450

# Kickstart Templates Don't Render FreelPA Snippet correctly

04/25/2014 03:03 PM - Stephen Benjamin

Status: Closed Priority: High

**Assignee:** Stephen Benjamin

Category: Templates

Target version: 1.5.0

Difficulty: Fixed in Releases:

Triaged: Found in Releases: 1.5.0

Bugzilla link: Red Hat JIRA:

**Pull request:** 

#### Description

In order to have backward compatibility with earlier versions of Foreman, the template checks if `@host.respond\_to? :otp`, but this doesn't work in safe mode, even after adding it to the Jail.

#### **Associated revisions**

#### Revision 77d9d699 - 04/28/2014 02:25 PM - Stephen Benjamin

fixes #5450 - add realm to params for 1.4-compatible use in templates

#### Revision 03118084 - 04/28/2014 02:57 PM - Stephen Benjamin

fixes #5450 - add realm to params for 1.4-compatible use in templates

(cherry picked from commit 77d9d699b32e735e4b70195e978de108a992d3f5)

### History

### #1 - 04/25/2014 03:54 PM - Stephen Benjamin

https://github.com/theforeman/community-templates/blob/master/kickstart/provision\_rhel.erb#L101

#### #2 - 04/27/2014 09:09 AM - Stephen Benjamin

@host.methods doesn't actually return all the available methods in the safe mode jail, which is why respond\_to? doesn't work as expected. Anyway, we're stuck with identifying a Realm-capable foreman version using only the features 1.4. This simply will cause the template not to render on < 1.5:

```
<% if @host.otp && @host.realm && @host.realm.realm_type == "FreeIPA" && os_major <= 6 -%>
```

The only way I see is to add something to 1.5 that lets us know we can do realms, but that still works on 1.4...so, as far as I can see, that means abusing an existing hash.

What about adding this to Host::Managed#info?

```
param["realm"] = realm.name if realm
```

#### Then:

```
<% if @host.params["realm"] && @host.otp && @host.realm.realm_type == "FreeIPA" && os_major <= 6 -%>
```

## #3 - 04/27/2014 09:18 AM - Stephen Benjamin

- Priority changed from Normal to High

Ah sorry, should be this, but same idea:

```
<% if @host.info["parameters"]["realm"] && @host.otp && @host.realm.realm_type == "FreeIPA" && os_major <= 6 -
%>
```

But anyway, as it stands in the RHEL KS template, the freeipa\_snippet will never be reached because of the failing respond\_to?

## #4 - 04/28/2014 09:34 AM - Stephen Benjamin

05/11/2024 1/2

- Status changed from New to Ready For Testing

## PR's:

https://github.com/theforeman/foreman/pull/1406

https://github.com/theforeman/community-templates/pull/76

## #5 - 04/28/2014 02:32 PM - Dominic Cleal

- Assignee set to Stephen Benjamin
- Target version set to 1.8.3
- translation missing: en.field\_release set to 4

# #6 - 04/28/2014 03:31 PM - Stephen Benjamin

- Status changed from Ready For Testing to Closed
- % Done changed from 0 to 100

Applied in changeset <u>77d9d699b32e735e4b70195e978de108a992d3f5</u>.

05/11/2024 2/2