

Smart Proxy - Bug #5561

foreman-proxy run puppet over ssh doesn't work

05/02/2014 07:27 PM - Anonymous

Status:	Closed	
Priority:	Normal	
Assignee:		
Category:	Puppet	
Target version:	1.5.0	
Difficulty:		Fixed in Releases:
Triaged:		Found in Releases:
Bugzilla link:	1103935	Red Hat JIRA:
Pull request:		

Description

Running foreman(1.4.3) and foreman-proxy (1.5.0-0) on RHEL 6.2, I found that the only way to get puppet run over ssh to work is to remove the space between `-l <user>` and `-i <keyfile>` in `puppet_ssh.rb`. Otherwise, the remote system shows this in the logs (X's added). Note the extra whitespace appearing before `foreman-proxy` user.

```
May  2 14:06:04 XXXXX sshd[2430]: Invalid user  foreman-proxy from X.X.X.X
May  2 14:06:04 XXXXX sshd[2431]: input_userauth_request: invalid user  foreman-proxy
May  2 14:06:04 XXXXX sshd[2430]: Failed none for invalid user  foreman-proxy from X.X.X.X port 34
970 ssh2
May  2 14:06:04 XXXXX sshd[2430]: Failed password for invalid user  foreman-proxy from X.X.X.X por
t 34970 ssh2
May  2 14:06:04 XXXXX sshd[2430]: Failed password for invalid user  foreman-proxy from X.X.X.X por
t 34970 ssh2
May  2 14:06:04 XXXXX sshd[2431]: Connection closed by X.X.X.X
```

Related settings look like:

```
:puppet: true
:puppet_provider: puppetssh
:puppetssh_sudo: false
:puppetssh_command: /usr/local/bin/puppet_with_sudo.sh
:puppetssh_user: foreman-proxy
:puppetssh_keyfile: /etc/foreman-proxy/ssh/id_rsa
```

If I change the code to the following, and restart, it runs just fine.

```
--- foreman-proxy/lib/proxy/puppet/puppet_ssh.rb.orig 2014-05-02 14:06:33.010472500 -0500
+++ foreman-proxy/lib/proxy/puppet/puppet_ssh.rb      2014-05-02 14:06:21.626366466 -0500
@@ -6,10 +6,10 @@
   cmd = []
   cmd.push(which('sudo')) if SETTINGS.puppetssh_sudo
   cmd.push(which('ssh'))
-  cmd.push("-l #{SETTINGS.puppetssh_user}") if SETTINGS.puppetssh_user
+  cmd.push("-l#{SETTINGS.puppetssh_user}") if SETTINGS.puppetssh_user
   if (file = SETTINGS.puppetssh_keyfile)
     if File.exists?(file)
-      cmd.push("-i #{file}")
+      cmd.push("-i#{file}")
     else
       logger.warn("Unable to access SSH private key:#{file}, ignoring...")
     end
```

Associated revisions

Revision 442e2bda - 05/09/2014 09:52 AM - Alyssa Hardy

fixes #5561 pass arguments correctly in run puppet over ssh

History

#1 - 05/04/2014 12:18 PM - Ohad Levy

would you mind sending a PR as well?

thanks!

#2 - 05/04/2014 08:18 PM - Anonymous

I'll be happy to provide more information, but what's a PR?

#3 - 05/05/2014 05:50 AM - Marek Hulán

PR stands for Pull Request on github. For more information how to do that, see [tutorial on our wiki](#)

#4 - 05/05/2014 05:46 PM - Anonymous

Thanks, PR created.

#5 - 05/06/2014 07:06 AM - Marek Hulán

- *Category set to Puppet*

- *Status changed from New to Ready For Testing*

Just for the reference, PR is here <https://github.com/foreman/smart-proxy/pull/154>

#6 - 05/09/2014 09:50 AM - Dominic Cleal

- *Target version set to 1.8.3*

- *translation missing: en.field_release set to 4*

#7 - 05/09/2014 10:52 AM - Anonymous

- *Status changed from Ready For Testing to Closed*

- *% Done changed from 0 to 100*

Applied in changeset [442e2bdaeca04a97cee499f23e75afe4a8923d9](#).

#8 - 06/02/2014 11:43 PM - Bryan Kearney

- *Bugzilla link set to https://bugzilla.redhat.com/show_bug.cgi?id=1103935*