

Smart Proxy - Bug #5561

foreman-proxy run puppet over ssh doesn't work

05/02/2014 07:27 PM - Anonymous

<div>Status:Closed</div> <div>Priority:Normal</div> <div>Assignee:</div> <div>Category:Puppet</div> <div>Target version:1.5.0</div> <div>Difficulty:</div> <div>Triaged:</div> <div>Bugzilla link:1103935</div> <div>Pull request:</div>	<div>Fixed in Releases:</div> <div>Found in Releases:</div> <div>Red Hat JIRA:</div>
<div>Description</div> <p>Running foreman(1.4.3) and foreman-proxy (1.5.0-0) on Rhel 6.2, I found that the only way to get puppet run over ssh to work is to remove the space between -l &lt;user&gt; and -i &lt;keyfile&gt; in puppet_ssh.rb. Otherwise, the remote system shows this in the logs (X's added). Note the extra whitespace appearing before foreman-proxy user.</p> <pre>May  2 14:06:04 XXXXX sshd[2430]: Invalid user  foreman-proxy from X.X.X.X May  2 14:06:04 XXXXX sshd[2431]: input_userauth_request: invalid user  foreman-proxy May  2 14:06:04 XXXXX sshd[2430]: Failed none for invalid user  foreman-proxy from X.X.X.X port 34970 ssh2 May  2 14:06:04 XXXXX sshd[2430]: Failed password for invalid user  foreman-proxy from X.X.X.X port 34970 ssh2 May  2 14:06:04 XXXXX sshd[2430]: Failed password for invalid user  foreman-proxy from X.X.X.X port 34970 ssh2 May  2 14:06:04 XXXXX sshd[2431]: Connection closed by X.X.X.X</pre> <p>Related settings look like:</p> <pre>:puppet: true :puppet_provider: puppetssh :puppetssh_sudo: false :puppetssh_command: /usr/local/bin/puppet_with_sudo.sh :puppetssh_user: foreman-proxy :puppetssh_keyfile: /etc/foreman-proxy/ssh/id_rsa</pre> <p>If I change the code to the following, and restart, it runs just fine.</p> <pre>--- foreman-proxy/lib/proxy/puppet/puppet_ssh.rb.orig      2014-05-02 14:06:33.010472500 -0500 +++ foreman-proxy/lib/proxy/puppet/puppet_ssh.rb          2014-05-02 14:06:21.626366466 -0500 @@ -6,10 +6,10 @@      cmd = []      cmd.push(which('sudo')) if SETTINGS.puppetssh_sudo      cmd.push(which('ssh')) -    cmd.push("-l #{SETTINGS.puppetssh_user}") if SETTINGS.puppetssh_user +    cmd.push("-l#{SETTINGS.puppetssh_user}") if SETTINGS.puppetssh_user      if (file = SETTINGS.puppetssh_keyfile)        if File.exists?(file) -        cmd.push("-i #{file}") +        cmd.push("-i#{file}")        else          logger.warn("Unable to access SSH private key:#{file}, ignoring...")        end      end</pre>	

Associated revisions

fixes #5561 pass arguments correctly in run puppet over ssh

## History

---

### #1 - 05/04/2014 12:18 PM - Ohad Levy

would you mind sending a PR as well?

thanks!

### #2 - 05/04/2014 08:18 PM - Anonymous

I'll be happy to provide more information, but what's a PR?

### #3 - 05/05/2014 05:50 AM - Marek Hulán

PR stands for Pull Request on github. For more information how to do that, see [tutorial on our wiki](#)

### #4 - 05/05/2014 05:46 PM - Anonymous

Thanks, PR created.

### #5 - 05/06/2014 07:06 AM - Marek Hulán

- *Category set to Puppet*

- *Status changed from New to Ready For Testing*

Just for the reference, PR is here <https://github.com/theforeman/smart-proxy/pull/154>

### #6 - 05/09/2014 09:50 AM - Dominic Cleal

- *Target version set to 1.8.3*

- *translation missing: en.field\_release set to 4*

### #7 - 05/09/2014 10:52 AM - Anonymous

- *Status changed from Ready For Testing to Closed*

- *% Done changed from 0 to 100*

Applied in changeset [442e2bdaeca04a97cee499f23e75afe4a8923d9](#).

### #8 - 06/02/2014 11:43 PM - Bryan Kearney

- *Bugzilla link set to https://bugzilla.redhat.com/show\_bug.cgi?id=1103935*