

Katello - Bug #6368

katello-devel-installer fails due to missing /etc/pki/pulp directory

06/24/2014 10:10 PM - Stephen Benjamin

| | |
|--|---------------------------------|
| Status: Duplicate | |
| Priority: Normal | |
| Assignee: Eric Helms | |
| Category: Installer | |
| Target version: Katello Recycle Bin | |
| Difficulty: easy | Fixed in Releases: |
| Triaged: | Found in Releases: |
| Bugzilla link: | Red Hat JIRA: |
| Pull request: | |
| Description | |
| <p>Something went wrong! Check the log for ERROR-level output The full log is at /var/log/katello-installer/katello-devel-installer.log [INFO 2014-06-24 15:01:38 verbose] All hooks in group post finished [ERROR 2014-06-24 15:01:38 verbose] Repeating errors encountered during run: [ERROR 2014-06-24 15:01:38 verbose] Cannot create /etc/pki/pulp/nodes; parent directory /etc/pki/pulp does not exist [ERROR 2014-06-24 15:01:38 verbose] /Stage[main]/Certs::Pulp_parent/File[/etc/pki/pulp/nodes]/ensure: change from absent to directory failed: Cannot create /etc/pki/pulp/nodes; parent directory /etc/pki/pulp does not exist</p> <p>mkdir the directory and re-run the installer works fine.</p> <p>This is a long standing issue in Puppet that they refuse to fix: https://projects.puppetlabs.com/issues/86. Thankfully, when feeding a File resource an array, it is intelligent enough to create them in the correct tree order, so we could feed it an array like tike this: ["\$pulp_pki_dir", "\$pulp_pki_dir/nodes"] or similar.</p> | |
| Related issues: | |
| Has duplicate Katello - Bug #7007: katello devel installer fails creating cer... | Closed 08/09/2014 |

History

#1 - 07/07/2014 11:23 AM - Eric Helms

- Assignee set to Eric Helms
- Target version set to 49
- Difficulty set to easy
- Triaged changed from No to Yes

#2 - 07/28/2014 08:44 AM - Eric Helms

- Target version changed from 49 to 54

#3 - 08/11/2014 09:17 AM - Justin Sherrill

- Status changed from New to Duplicate

Duplicate of 7007

#4 - 08/11/2014 09:21 AM - Anonymous

- Has duplicate Bug #7007: katello devel installer fails creating certs in /etc/pki/pulp/nodes/ because /etc/pki/pulp doesn't exist yet added

#5 - 08/22/2014 08:58 AM - Eric Helms

- translation missing: en.field_release set to 13

#6 - 03/21/2015 11:03 AM - Eric Helms

- translation missing: en.field_release deleted (13)

#7 - 07/08/2016 11:20 AM - Eric Helms

- translation missing: en.field_release set to 166