

## Foreman - Bug #6834

### Missing ipappend from default PXE template

07/30/2014 05:43 AM - Dominic Cleal

<b>Status:</b>	New	
<b>Priority:</b>	Normal	
<b>Assignee:</b>		
<b>Category:</b>	Templates	
<b>Target version:</b>		
<b>Difficulty:</b>		<b>Fixed in Releases:</b>
<b>Triaged:</b>		<b>Found in Releases:</b>
<b>Bugzilla link:</b>	1124385	<b>Red Hat JIRA:</b>
<b>Pull request:</b>		

#### Description

Cloned from [https://bugzilla.redhat.com/show\\_bug.cgi?id=1124385](https://bugzilla.redhat.com/show_bug.cgi?id=1124385)

Description of problem:

When creating a default PXE menu, there is a missing option "ipappend 2"

Version-Release number of selected component (if applicable):

How reproducible:

100%

Steps to Reproduce:

1. Click "Build PXE default"
2. Examine `/var/lib/tftpboot/pxelinux.cfg/default`
3. Note the missing "ipappend 2"

Actual results:

ipappend 2 is missing

Expected results:

ipappend is there

Additional info:

```
--- PXELinux_default.erb.old 2014-07-29 10:15:00.486191538 +0000
```

```
+++ PXELinux_default.erb 2014-07-29 10:15:09.430191532 +0000
```

```
@ -23,6 +23,7 @
```

```
<% case profile[:hostgroup].operatingsystem.pxe_type -%>
```

```
<% when 'kickstart' -%>
```

```
append initrd=<%= profile[:hostgroup].operatingsystem.initrd(profile[:hostgroup].architecture)
> ks=<
= default_template_url(profile[:template], profile[:hostgroup]) %> ksdevice=bootif network kssendm
ac
```

```
+ ipappend 2
```

```
<% when 'preseed' -%>
```

```
append initrd=<%= profile[:hostgroup].operatingsystem.initrd(profile[:hostgroup].architecture)
> interface=auto url=<
= default_template_url(profile[:template], profile[:hostgroup]) %> ramdisk_size=10800 root=/dev/rd
/0 rw auto hostname=unassigned-hostname locale=en_US console-setup/ask_detect=false console-setup/
layout=USA console-setup/variant=USA
```

## History

---

**#1 - 07/30/2014 05:43 AM - Dominic Cleal**

- *Category set to Templates*
- *Assignee deleted (Dominic Cleal)*