

Foreman - Refactor #6857

optimize two-pane loading time by not render the entire layout

07/31/2014 05:12 AM - Ohad Levy

Status:	Closed	
Priority:	Normal	
Assignee:	Ohad Levy	
Category:	Web Interface	
Target version:	1.6.0	
Difficulty:		Fixed in Releases:
Triaged:		Found in Releases:
Bugzilla link:		Red Hat JIRA:
Pull request:	https://github.com/theforeman/foreman/pull/1635	
Description		
when using two-panes, the layout is dropped and never used, we can skip generating it on the server side and improve page load time.		

Associated revisions

Revision 1dd18c34 - 08/05/2014 07:54 AM - Ohad Levy

fixes #6857 improve two-pane load times

History

#1 - 07/31/2014 05:13 AM - The Foreman Bot

- Status changed from New to Ready For Testing
- Pull request <https://github.com/theforeman/foreman/pull/1635> added
- Pull request deleted ()

#2 - 08/05/2014 07:15 AM - Dominic Cleal

- translation missing: en.field_release set to 10

#3 - 08/05/2014 08:01 AM - Ohad Levy

- Status changed from Ready For Testing to Closed
- % Done changed from 0 to 100

Applied in changeset [1dd18c340e1a43feb3280a8e680324d59ff32b49](#).