

Installer - Bug #6910

"ddns-update-style none;" set by foreman-installer while manual states "ddns-update-style interim;"

08/04/2014 07:46 AM - Jorick Astrego

Status: Resolved	
Priority: Normal	
Assignee:	
Category: Foreman modules	
Target version:	
Difficulty:	Fixed in Releases:
Triaged: No	Found in Releases: Nightly
Bugzilla link:	Red Hat JIRA:
Pull request:	
Description	
foreman-installer sets "ddns-update-style none;", while the manual (http://www.theforeman.org/manuals/1.5/index.html#4.3.ISCDHCP) states "ddns-update-style interim;"	
Even when already configured it gets overwritten	
<pre>[WARN 2014-08-04 12:48:27 main] /Stage[main]/Dhcp/File[/etc/dhcp]/mode: mode changed '0750' to '0755' [INFO 2014-08-04 12:48:27 main] RESOURCE File[/etc/dhcp] [DEBUG 2014-08-04 12:48:27 main] /Stage[main]/Dhcp/File[/etc/dhcp]: The container Class[Dhcp] will propagate my refresh event [DEBUG 2014-08-04 12:48:27 main] Executing 'diff -u /etc/dhcp/dhcpd.conf /tmp/puppet-file20140804-3766-91otdm-0' [WARN 2014-08-04 12:48:27 main] /Stage[main]/Dhcp/File[/etc/dhcp/dhcpd.conf]/content: [INFO 2014-08-04 12:48:27 main] --- /etc/dhcp/dhcpd.conf 2013-11-22 15:30:00.000000000 +0100 [INFO 2014-08-04 12:48:27 main] +++ /tmp/puppet-file20140804-3766-91otdm-0 2014-08-04 12:48:27.236000034 +0200 [INFO 2014-08-04 12:48:27 main] @ -1,5 +1,39 @ [INFO 2014-08-04 12:48:27 main] -# [INFO 2014-08-04 12:48:27 main] -# DHCP Server Configuration file. [INFO 2014-08-04 12:48:27 main] -# see /usr/share/doc/dhcp*/dhcpd.conf.sample [INFO 2014-08-04 12:48:27 main] -# see 'man 5 dhcpd.conf' [INFO 2014-08-04 12:48:27 main] -# [INFO 2014-08-04 12:48:27 main] +# dhcpd.conf [INFO 2014-08-04 12:48:27 main] +omapi-port 7911; [INFO 2014-08-04 12:48:27 main] + [INFO 2014-08-04 12:48:27 main] +default-lease-time 600; [INFO 2014-08-04 12:48:27 main] +max-lease-time 7200; [INFO 2014-08-04 12:48:27 main] + [INFO 2014-08-04 12:48:27 main] + [INFO 2014-08-04 12:48:27 main] +ddns-update-style none;* [INFO 2014-08-04 12:48:27 main] + [INFO 2014-08-04 12:48:27 main] +option domain-name "test.nu"; [INFO 2014-08-04 12:48:27 main] +option domain-name-servers *.***.***.***; [INFO 2014-08-04 12:48:27 main] + [INFO 2014-08-04 12:48:27 main] +allow booting; [INFO 2014-08-04 12:48:27 main] +allow bootp;</pre>	

History

#1 - 08/04/2014 07:52 AM - Dominic Cleal

- Project changed from Packaging to Installer

- Category set to Foreman modules

It's not really relevant for Foreman, but sure, we could have it parameterised.

#2 - 08/04/2014 09:40 AM - Jorick Astrego

If it's not relevant for foreman why does the installer overwrite this parameter in the dhcpd.conf or why put it in the manual differently.

I know it says example but it's hard enough to set everything correct on the parameters that are relevant ;-)

#3 - 08/04/2014 09:44 AM - Dominic Cleal

The installer is Puppet based and simply templates the whole file.

<https://github.com/theforeman/puppet-dhcp/blob/master/templates/dhcpd.conf.erb#L7> seems it already is parameterised in that module, but https://github.com/theforeman/puppet-foreman_proxy/blob/master/manifests/proxydhcp.pp#L20 doesn't use it or the \$foreman_proxy::dhcp_key_name parameter.

#4 - 12/02/2020 05:34 PM - Ewoud Kohl van Wijngaarden

- *Status changed from New to Resolved*

It is possible to set dhcp::dnsupdatekey via custom-hiera.yaml. Given its age I'm going to close this.