

## Smart Proxy - Bug #6945

### smart-proxy doesn't find the autosign.conf if not at "#{puppetdir}/autosign.conf"

08/05/2014 03:19 PM - Brian Witt

<b>Status:</b> Closed	
<b>Priority:</b> Normal	
<b>Assignee:</b>	
<b>Category:</b> Puppet	
<b>Target version:</b>	
<b>Difficulty:</b>	<b>Fixed in Releases:</b>
<b>Triaged:</b>	<b>Found in Releases:</b>
<b>Bugzilla link:</b>	<b>Red Hat JIRA:</b>
<b>Pull request:</b> <a href="https://github.com/foreman/smart-proxy/pull/530">https://github.com/foreman/smart-proxy/pull/530</a>	
<b>Description</b>	
modules/puppetca/puppetca.rb hardcodes the autosign.conf file to	
<pre>def autosign_file   "#{puppetdir}/autosign.conf" end</pre>	
so even if we've set a different location in puppet.conf:	
<pre>autosign = /etc/autosign.conf { mode = 664 }</pre>	
we still see this error in the foreman-proxy logs:	
No such file /etc/puppet/autosign.conf	

#### Associated revisions

##### Revision e7968a9d - 05/30/2017 08:07 AM - Michael Moll

Fixes #6945 - use autosign path for puppetca

#### History

##### #1 - 08/05/2014 03:22 PM - Brian Witt

Our puppetdir in this case is set to /etc/puppet. Is there anything else that uses puppetdir?

##### #2 - 08/06/2014 03:43 AM - Dominic Cleal

- Category set to Puppet

Brian Witt wrote:

Our puppetdir in this case is set to /etc/puppet. Is there anything else that uses puppetdir?

Yes, it's also used to find puppet.conf, they're expected to be in the same directory.

##### #3 - 08/06/2014 08:41 AM - Brian Witt

I thought the puppet.conf location was set via :puppet\_conf:

##### #4 - 08/06/2014 08:45 AM - Dominic Cleal

Brian Witt wrote:

I thought the puppet.conf location was set via :puppet\_conf:

Yeah, puppet\_conf will override the use of puppetdir/puppet.conf, so you can change puppetdir safely if you have puppet\_conf set.

**#5 - 05/20/2017 12:26 PM - Anonymous**

I'm leaning towards closing this.

**#6 - 05/20/2017 04:11 PM - Brian Witt**

Michael Moll wrote:

I'm leaning towards closing this.

Why?

**#7 - 05/20/2017 05:13 PM - Anonymous**

I'd say it "works as designed". Maybe the docs would need updating...

**#8 - 05/23/2017 04:09 PM - Anonymous**

I think I need to revise my opinion on that in the light of the whole Puppet 4 situation now. It seems the puppetdir setting is not used elsewhere in the puppetca module.

**#9 - 05/23/2017 06:18 PM - The Foreman Bot**

- Status changed from New to Ready For Testing
- Assignee set to Anonymous
- Pull request <https://github.com/theforeman/smart-proxy/pull/530> added

**#10 - 05/30/2017 09:01 AM - Anonymous**

- Status changed from Ready For Testing to Closed
- % Done changed from 0 to 100

Applied in changeset [e7968a9dc616e1c4c28961c1b3cd182eb02c1831](#).

**#11 - 05/31/2017 01:04 AM - Brian Witt**

Thanks!