

Foreman - Bug #6952

Correctly set hostgroup after provisioning from PXE menu

08/06/2014 06:19 AM - Dominic Cleal

Status:	Closed	
Priority:	Normal	
Assignee:	Amir Fefer	
Category:	Puppet integration	
Target version:	1.15.0	
Difficulty:		Fixed in Releases:
Triaged:		Found in Releases:
Bugzilla link:	1127164	Red Hat JIRA:
Pull request:	https://github.com/foreman/foreman/pull/4112	

Description

Cloned from https://bugzilla.redhat.com/show_bug.cgi?id=1127164

Description of problem:
When we provision from the standard PXE menu, we can choose which hostgroup template to install the new server from.

Version-Release number of selected component (if applicable):
6 beta

How reproducible:
always

Steps to Reproduce:

1. Create some hostgroups with associated content views and lifecycle environments
2. Build the PXE default menu from the Provisioning Templates screen
3. PXE boot a new server
4. From the boot menu, select a hostgroup boot option

Actual results:
Machine boots and installs, however once it has registered with foreman, it is not in a hostgroup

Expected results:
The newly installed machine should be in the same hostgroup that we selected in the PXE menu.

Additional info:
Candidate patch:

```
patch p0 -t f << EOF
- /usr/share/foreman/app/models/host/managed.rb 2014-08-06 08:24:18.912311511 0000
++ /usr/share/foreman/app/models/host/managed.rb 2014-08-06 09:06:02.716311124 +0000
@ -404,6 +404,14 @
host ||= Host.new(:name => hostname, :certname => certname) if Setting[:create_new_host_when_facts_uploaded]

return Host.new, true if host.nil?

# set hostgroup defaults if provided by a fact
+ hostgroup_fact='foreman_hostgroup'
+ if facts.keys.include?(hostgroup_fact)
+   host.hostgroup = Hostgroup.find_by_title(facts[hostgroup_fact])
+   host.set_hostgroup_defaults
+ end
+

1. if we were given a certname but found the Host by hostname we should update the certname
   host.certname = certname if certname.present?

EOF
```

Related issues:

Related to Foreman - Bug #19635: Foreman host hostgroup is changed on puppet ...

Resolved**Associated revisions****Revision 9883149a - 01/11/2017 06:42 AM - Amir Fefer**

Fixes #6952 - Set hostgroup after provisioning from pxe

After hostgroup provisioning, when the machine has registered with foreman, it should be in the same hostgroup. to achieve this behavior, the fact foreman_hostgroup should be added to hostgroup provisioning template

History**#1 - 08/06/2014 06:20 AM - Dominic Cleal***- Category set to Puppet integration***#2 - 03/22/2016 04:34 AM - Ohad Levy***- Assignee set to Amir Fefer***#3 - 12/14/2016 07:04 PM - The Foreman Bot***- Status changed from New to Ready For Testing**- Pull request <https://github.com/theforeman/foreman/pull/4112> added***#4 - 01/11/2017 07:01 AM - Amir Fefer***- Status changed from Ready For Testing to Closed**- % Done changed from 0 to 100*Applied in changeset [9883149acbb88bd59695b92207933c074a72c427](#).**#5 - 01/12/2017 03:21 AM - Dominic Cleal***- translation missing: en.field_release set to 209***#6 - 01/24/2017 09:59 AM - Daniel Lobato Garcia***- Target version set to 169***#7 - 02/18/2017 10:23 AM - Brad Buckingham***- Target version deleted (169)***#8 - 02/21/2017 09:54 AM - Daniel Lobato Garcia***- Target version set to 1.11.0***#9 - 05/24/2017 06:26 AM - Dominic Cleal***- Related to Bug #19635: Foreman host hostgroup is changed on puppet run and fact import added*