

Katello - Bug #7005

Unable to delete host tied back to activation key

08/09/2014 09:18 AM - Brad Buckingham

Status: Closed	
Priority: Normal	
Assignee:	
Category: Web UI	
Target version: Katello 2.0	
Difficulty:	Fixed in Releases:
Triaged: Yes	Found in Releases:
Bugzilla link: 1122736	Red Hat JIRA:
Pull request: https://github.com/Katello/katello/pull/455 5	
Description Cloned from https://bugzilla.redhat.com/show_bug.cgi?id=1122736 Description of problem: I tried to delete a host and received a trace. Afterwards I could not view the host details though I could see it in the host list Version-Release number of selected component (if applicable): ruby193-rubygem-katello-1.5.0-65.el6sat.noarch How reproducible: Uncertain, but based on the additional info, probably always Steps to Reproduce: 1. Create an Activation Key 2. Create a Host and include the activation key Actual results: Can't delete the host without error Expected results: Host should delete as expected Additional info: I had to do the following: delete from hosts where id = 7; ERROR: update or delete on table "hosts" violates foreign key constraint "katello_systems_host_id" on table "katello_systems" DETAIL: Key (id)=(7) is still referenced from table "katello_systems". delete from katello_systems where id = 11; ERROR: update or delete on table "katello_systems" violates foreign key constraint "system_activation_keys_system_id_fk" on table "katello_system_activation_keys" DETAIL: Key (id)=(11) is still referenced from table "katello_system_activation_keys". foreman=# delete from katello_system_activation_keys where id = 11; DELETE 1 foreman=# delete from katello_systems where id = 11; DELETE 1 foreman=# delete from hosts where id = 7; DELETE 1 foreman=# \q	
Related issues: Is duplicate of Katello - Bug #6898: deleteing a host does not delete a conte... Duplicate 08/04/2014	

Associated revisions

Revision 73ef39f4 - 08/09/2014 09:26 AM - Brad Buckingham

fixes #7005 / BZ 1122736 - content host - change registration behavior with foreman host

This commit alters the behavior of registering a content host (with or without an activation key) that is to be associated with a foreman host to do the following:

1. identify the foreman host that this content host will be associated with by both name and mac address (previously it was only by name)
2. if the foreman host identified is already associated with a content host, delete it and then create/associate a new one. (This will avoid there becoming duplicate content hosts with the same name.)

Revision cda8940a - 08/12/2014 03:20 PM - Brad Buckingham

Merge pull request #4555 from bbuckingham/issue-7005

fixes #7005 / BZ 1122736 - content host - change registration behavior with foreman host

History

#1 - 08/09/2014 09:29 AM - The Foreman Bot

- Status changed from New to Ready For Testing
- Target version set to 54
- Pull request <https://github.com/Katello/katello/pull/4555> added
- Pull request deleted ()

#2 - 08/12/2014 04:01 PM - Brad Buckingham

- Status changed from Ready For Testing to Closed
- % Done changed from 0 to 100

Applied in changeset [katello|73ef39f42f7df66b7abbd7b293d4928cefacc6e9d](#).

#3 - 08/14/2014 08:54 AM - Eric Helms

- Triaged changed from No to Yes

#4 - 08/15/2014 01:48 PM - Brad Buckingham

- Is duplicate of Bug #6898: deleting a host does not delete a content host, generates a FK constrain error added

#5 - 08/22/2014 09:25 AM - Eric Helms

- translation missing: en.field_release set to 13