

Katello - Bug #7119

Host Collection actions selects all available hosts if collection name has spaces in them

08/15/2014 04:41 PM - Walden Raines

Status:	Closed	
Priority:	Normal	
Assignee:	Walden Raines	
Category:	Web UI	
Target version:	Katello 2.0	
Difficulty:	easy	Fixed in Releases:
Triaged:	Yes	Found in Releases:
Bugzilla link:	1130645	Red Hat JIRA:
Pull request:	https://github.com/Katello/katello/pull/4597	

Description

Cloned from https://bugzilla.redhat.com/show_bug.cgi?id=1130645

Description of problem:

Created a host collection named 'RHEL 6 x86_64' and added one of my 2 content hosts to it. I then went to Host Collections, chose content_view:'RHEL 6 x86_64' and tried to install a package by choosing the "Package Installation, Removal, and Update" from the Collection Actions tab. I noticed that all my existing content hosts were being selected (see attached screenshot).

I then renamed my host collection to 'foo' and tried it again. This time only the one content host associated with 'foo' were selected/displayed.

Version-Release number of selected component (if applicable):

Browser:

- Firefox 31.0 Mac OS

Build:

- Satellite-6.0.4-RHEL-6-20140813.2

Packages:

- candlepin-0.9.23-1.el7.noarch
- candlepin-common-1.0.1-1.el7.noarch
- candlepin-guice-3.0-2_redhat_1.el7.noarch
- candlepin-scl-1-5.el7.noarch
- candlepin-scl-quartz-2.1.5-6.el7.noarch
- candlepin-scl-rhino-1.7R3-3.el7.noarch
- candlepin-scl-runtime-1-5.el7.noarch
- candlepin-selinux-0.9.23-1.el7.noarch
- candlepin-tomcat-0.9.23-1.el7.noarch
- elasticsearch-0.90.10-4.el7sat.noarch
- foreman-1.6.0.40-1.el7sat.noarch
- foreman-compute-1.6.0.40-1.el7sat.noarch
- foreman-gce-1.6.0.40-1.el7sat.noarch
- foreman-libvirt-1.6.0.40-1.el7sat.noarch
- foreman-ovirt-1.6.0.40-1.el7sat.noarch
- foreman-postgresql-1.6.0.40-1.el7sat.noarch
- foreman-proxy-1.6.0.27-1.el7sat.noarch
- foreman-selinux-1.6.0.6-1.el7sat.noarch
- foreman-vmware-1.6.0.40-1.el7sat.noarch
- katello-1.5.0-28.el7sat.noarch

- katello-ca-1.0-1.noarch
- katello-certs-tools-1.5.6-1.el7sat.noarch
- katello-installer-0.0.59-1.el7sat.noarch
- openldap-2.4.39-3.el7.x86_64
- pulp-katello-0.3-3.el7sat.noarch
- pulp-nodes-common-2.4.0-0.30.beta.el7sat.noarch
- pulp-nodes-parent-2.4.0-0.30.beta.el7sat.noarch
- pulp-puppet-plugins-2.4.0-0.30.beta.el7sat.noarch
- pulp-puppet-tools-2.4.0-0.30.beta.el7sat.noarch
- pulp-rpm-plugins-2.4.0-0.30.beta.el7sat.noarch
- pulp-selinux-2.4.0-0.30.beta.el7sat.noarch
- pulp-server-2.4.0-0.30.beta.el7sat.noarch
- python-ldap-2.4.6-6.el7.x86_64
- ruby193-rubygem-net-ldap-0.3.1-3.el7sat.noarch
- ruby193-rubygem-runcible-1.1.0-2.el7sat.noarch
- rubygem-hammer_cli-0.1.1-11.el7sat.noarch
- rubygem-hammer_cli_foreman-0.1.1-15.el7sat.noarch
- rubygem-hammer_cli_foreman_tasks-0.0.3-3.el7sat.noarch
- rubygem-hammer_cli_katello-0.0.4-12.el7sat.noarch

How reproducible:

Steps to Reproduce:

1. Make sure to have more than one content host
2. Create a new host collection and name it 'RHEL 6 x86_64'
3. Add one one of your existing content hosts to this host collection
4. Select the 'RHEL 6 x86_64' host collection and then attempt to perform one of the available actions from the Collection Actions tab

Actual results:

All available content hosts are selected

Expected results:

Only the one content host associated to 'RHEL 6 x86_64' should be selected/displayed

Additional info:

```
> /var/log/foreman/production.log <
Processing by Katello::Api::V2::HostCollectionsController#show as JSON
Parameters: {"fields"=>"full", "api_version"=>"v2", "id"=>"2"}
Rendered /opt/rh/ruby193/root/usr/share/gems/gems/katello-1.5.0/app/views/katello/api/v2/host_collections/show.json.rabl within
katello/api/v2/layouts/resource (4.4ms)
Completed 200 OK in 12ms (Views: 5.0ms | ActiveRecord: 1.4ms)
Processing by Katello::Api::V2::SystemsController#index as JSON
Parameters: {"page"=>"1", "paged"=>"true", "search"=>"", "sort_by"=>"name", "sort_order"=>"ASC", "api_version"=>"v2",
"host_collection_id"=>"2"}
```

Associated revisions

Revision 37df2d9d - 08/20/2014 04:02 PM - Walden Raines

Fixes #7119/BZ1130645: double quote host collection name in search.

The host collection search was using single quotes which search isn't happy with. This commit changes the host collection bulk actions to use double quotes.

<http://projects.theforeman.org/issues/7119>
https://bugzilla.redhat.com/show_bug.cgi?id=1130645

Revision 06bd1e73 - 08/20/2014 04:02 PM - Walden Raines

Fixes #7119/BZ1130645: double quote host collection name in search.

The host collection search was using single quotes which search isn't happy with. This commit changes the host collection bulk actions to use double quotes.

<http://projects.theforeman.org/issues/7119>

Revision 57c81002 - 08/21/2014 11:35 AM - Walden Raines

Merge pull request #4597 from waldenraines/7119

Fixes #7119/BZ1130645: double quote host collection name in search.

History

#1 - 08/17/2014 02:27 PM - Eric Helms

- Target version set to 55
- Difficulty set to easy
- Triaged changed from No to Yes

#2 - 08/20/2014 04:04 PM - The Foreman Bot

- Status changed from New to Ready For Testing
- Pull request <https://github.com/Katello/katello/pull/4597> added
- Pull request deleted ()

#3 - 08/21/2014 12:01 PM - Walden Raines

- Status changed from Ready For Testing to Closed
- % Done changed from 0 to 100

Applied in changeset [katello|37df2d9d4eb0162e643eca4fe6abf679b8f4b4f7.](#)

#4 - 08/22/2014 09:30 AM - Eric Helms

- translation missing: en.field_release set to 13