

Foreman - Bug #727

next_ip function always overwrites the ip address even if it has already been entered

03/12/2011 08:44 AM - Paul Kelly

Status: Duplicate	
Priority: Normal	
Assignee: Paul Kelly	
Category: Web Interface	
Target version: 1.0	
Difficulty:	Fixed in Releases:
Triaged:	Found in Releases:
Bugzilla link:	Red Hat JIRA:
Pull request:	
Description	
Related issues:	
Related to Foreman - Feature #1062: The automatic loading of next ip when a s...	Rejected 07/23/2011
Related to Foreman - Bug #1374: IP overwritten if you select a subnet	Closed 12/06/2011

History

#1 - 03/12/2011 08:53 AM - Paul Kelly

- Status changed from New to Ready For Testing

Provides a new option to observe_field, :if_empty, which only overwrites the target if this field is not already filled

#2 - 11/17/2011 03:46 AM - Ohad Levy

- Status changed from Ready For Testing to New

- Assignee changed from Paul Kelly to Amos Benari

- Target version set to 0.4.1

#3 - 12/19/2011 07:39 AM - Paul Kelly

- Status changed from New to Ready For Testing

#4 - 12/25/2011 03:47 AM - Ohad Levy

- Status changed from Ready For Testing to Duplicate

- Assignee changed from Amos Benari to Paul Kelly

- Target version changed from 0.4.1 to 1.0

fixed as part of [#1374](#)