

## Foreman - Feature #7828

### Provide base URL of Foreman via foreman\_url

10/07/2014 03:54 AM - Lukas Zapletal

<b>Status:</b> Duplicate	
<b>Priority:</b> Normal	
<b>Assignee:</b>	
<b>Category:</b> Templates	
<b>Target version:</b>	
<b>Difficulty:</b>	<b>Fixed in Releases:</b>
<b>Triaged:</b>	<b>Found in Releases:</b> 1.6.0
<b>Bugzilla link:</b> 1176111	<b>Red Hat JIRA:</b>
<b>Pull request:</b>	
<b>Description</b>	
We currently can't use foreman_url in PXELinux Global Default or similar templates, because there is no @host accessible, therefore it leads to <b>failed to process template: undefined method `token' for nil:NilClass</b> errors.	
We can easily allow this by skipping the token when @host attribute is not available.	
<b>Related issues:</b>	
Related to Foreman - Bug #11723: Build PXE Default fails with error	<b>Closed</b> <b>09/08/2015</b>
Related to Foreman - Bug #14232: Missing variable to include Sat 6 Hostname i...	<b>Closed</b> <b>03/16/2016</b>
Related to Foreman - Feature #14245: Create new template helper setting('glob...	<b>New</b> <b>03/17/2016</b>

### History

#### #1 - 10/08/2014 05:34 AM - The Foreman Bot

- Status changed from New to Ready For Testing
- Pull request <https://github.com/theforeman/foreman/pull/1827> added
- Pull request deleted ()

#### #2 - 12/19/2014 11:18 AM - Bryan Kearney

- Bugzilla link set to 1176111

#### #3 - 09/10/2015 04:13 AM - Dominic Cleal

- Tracker changed from Bug to Feature
- Status changed from Ready For Testing to New
- Assignee deleted (Lukas Zapletal)
- Target version deleted (1.7.2)
- Pull request added
- Pull request deleted (<https://github.com/theforeman/foreman/pull/1827>)

#### #4 - 09/10/2015 04:26 AM - Dominic Cleal

- Related to Bug #11723: Build PXE Default fails with error added

#### #5 - 09/10/2015 04:28 AM - Dominic Cleal

- Subject changed from Allow foreman\_url to be used in generic templates to Provide base URL of Foreman via foreman\_url

[#11723](#) sort of replaces this, permitting use of foreman\_url in a default template. Changing this ticket to match <https://github.com/theforeman/foreman/pull/1827#issuecomment-68529530> which asks for a way to have foreman\_url return the base URL.

#### #6 - 03/16/2016 01:05 PM - Marek Hulán

- Related to Bug #14232: Missing variable to include Sat 6 Hostname in PXE Menus added

**#7 - 03/16/2016 01:10 PM - Marek Hulán**

- Status changed from New to Duplicate

The @host problem was already solved by [#11723](#), foreman\_url is still not usable with safe mode though, which should be fixed by [#14232](#). Also instead of using foreman\_url('base') we introduce new method called foreman\_server\_fqdn that wouldn't contain protocol. If you'd still want to add foreman\_url('base') support please reopen or comment in [#14232](#) which could probably incorporate it as well.

**#8 - 03/17/2016 03:31 AM - Lukas Zapletal**

- Related to Feature #14245: Create new template helper setting('global\_setting\_name') added

**#9 - 03/17/2016 03:32 AM - Lukas Zapletal**

The new method is fine, thanks.