

## Foreman - Bug #861

### foreman shows blank page on initial startup from non web-brick start

04/20/2011 06:07 PM - Corey Osman

<b>Status:</b> Closed	
<b>Priority:</b> Normal	
<b>Assignee:</b>	
<b>Category:</b>	
<b>Target version:</b>	
<b>Difficulty:</b>	<b>Fixed in Releases:</b>
<b>Triaged:</b>	<b>Found in Releases:</b>
<b>Bugzilla link:</b>	<b>Red Hat JIRA:</b>
<b>Pull request:</b>	
<b>Description</b>	
<p>I added an apache vhost for foreman and then started httpd. When I went to <a href="http://foreman:3000">http://foreman:3000</a> I only received a blank page. I figured something hadn't triggered so I stopped httpd. I then fired up foreman via <code>script/server -e production</code> in order to initialize the database that was empty. Once I saw the foreman homepage I stopped the web brick server and restarted httpd. Everything works as expected via apache now after initializing via web brick.</p> <p>Maybe it has something to do with the <code>-e production</code> being available in apache?</p>	

#### History

#1 - 04/20/2011 06:08 PM - Corey Osman

Maybe it has something to do with the `-e production` being available in apache?

should be

Maybe it has something to do with the `-e production` **NOT** being available in apache?

#2 - 04/21/2011 07:01 AM - Ohad Levy

- Status changed from New to Feedback

how are you using it?

the best way would be to use something such as passenger(see example puppet module for foreman), my guess is that your apache instance has no access to your db.

#3 - 05/02/2011 05:35 AM - Ohad Levy

- Status changed from Feedback to Closed