

## Installer - Bug #8942

### allow root directory parameter to be overridden in tftp puppet module

01/13/2015 05:33 PM - Greg Petras

<b>Status:</b> Closed	
<b>Priority:</b> Normal	
<b>Assignee:</b>	
<b>Category:</b> Foreman modules	
<b>Target version:</b>	
<b>Difficulty:</b>	<b>Fixed in Releases:</b>
<b>Triaged:</b>	<b>Found in Releases:</b>
<b>Bugzilla link:</b>	<b>Red Hat JIRA:</b>
<b>Pull request:</b>	
<b>Description</b> Currently the tftp module does not correctly allow the root parameter to be overridden when using the foreman_proxy module to configure foreman unless you use Hiera overrides for tftp::params::root. This should be fixed so that foreman_proxy::params references tftp::root, and tftp::root is the configurable parameter for the TFTP root.	

#### Associated revisions

---

**Revision c0bc540d - 01/14/2015 11:44 AM - Greg Petras**

fixes #8942 - ability to override tftp root parameter

**Revision 837bfccb - 01/15/2015 05:12 AM - Greg Petras**

fixes #8942 - ability to override tftp root parameter

Fixes GH-138

#### History

---

**#1 - 01/14/2015 06:02 PM - Anonymous**

- Status changed from New to Closed

- % Done changed from 0 to 100

Applied in changeset [puppet-tftp|c0bc540d542ea2f2e037aad4926b32dc64d685f1](#).