

## Foreman - Bug #9115

### Inconsistent format of results of GET /api/puppetclasses

01/26/2015 09:23 AM - Martin Bacovsky

<b>Status:</b>	New	
<b>Priority:</b>	Normal	
<b>Assignee:</b>		
<b>Category:</b>	API	
<b>Target version:</b>		
<b>Difficulty:</b>		<b>Fixed in Releases:</b>
<b>Triaged:</b>		<b>Found in Releases:</b>
<b>Bugzilla link:</b>		<b>Red Hat JIRA:</b>
<b>Pull request:</b>		

#### Description

In API the list of puppet classes returns results in format that is inconsistent with the rest of the API.

```
"results" => {
  "apache" => [
    [ 0 ] {
      "id" => 8,
      "name" => "apache",
      "created_at" => "2014-10-08T11:39:06Z",
      "updated_at" => "2014-10-08T11:39:06Z"
    },
    [ 1 ] {
      "id" => 69,
      "name" => "apache::confd::no_accf",
      "created_at" => "2014-10-08T11:39:07Z",
      "updated_at" => "2014-10-08T11:39:07Z"
    },
  ],
}
```

The individual classes are nested under the module name, which makes automation difficult. I'm not sure what is the background for this deviation from usual format, but it seems that adding module name as an attribute of the class would do the job.

#### History

##### #1 - 01/26/2015 10:42 AM - Ohad Levy

yes this is known, I think we can only fix it in api v3.