Foreman - Bug #9782

Using media_path in Templates does not resolve properly

03/16/2015 09:17 AM - Mattias Giese

Status: Closed

Priority: Normal

Assignee:

Category: Templates

Target version: 1.11.1

Difficulty:

Triaged: Found in Releases: 1.8.0

Bugzilla link: Red Hat JIRA:

Pull request: https://github.com/theforeman/foreman/p

ull/3347,

https://github.com/theforeman/communit

y-templates/pull/256

Description

Using <%= media path %> in provisioning templates always resolves to '/media'.

From the IRC:

<snip>

14:08:29 Dominic | lowercase: yeah, I can reproduce that, I guess something is leaking in from Rails as it has a "media_path" that | would link to our installation media page - I suppose that's the result you're getting. Could you file that | please?

Fixed in Releases:

[...]

14:11:05 Dominic | as a workaround you can use: <%= @host.os.medium uri(@host) >

14:11:18 Dominic | (that's what the media path helper calls)

14:12:10 Dominic | or <= @mediapath %> actually, I think that's also the same, it's what we use in the kickstarts

</snip>

Related issues:

Related to Foreman - Bug #12791: The architecture is not interpolated for the...

Closed 12/12/2015

Related to Foreman - Refactor #14319: Remove media_path template helper which...

Closed 03/22/2016

Related to Foreman - Bug #15709: SLES doesn't get mediapath set in PXELinux c...

Closed 07/15/2016

Associated revisions

Revision 47306918 - 05/20/2015 07:37 PM - Michael Moll

refs #9782 - SUSE: usage of mediapath in PXELinux

Revision 7aa342ea - 03/30/2016 04:53 AM - Michael Moll

fixes #9782 - implement mediapath for suse/yast

Revision 62b5db1a - 04/06/2016 12:42 PM - Michael Moll

refs #9782 - implement mediapath for suse/yast

Revision 0f677011 - 04/18/2016 01:45 PM - Michael Moll

fixes #9782 - implement mediapath for suse/yast

(cherry picked from commit 7aa342eabf33f96916f3061db313aecba46b0933)

History

#1 - 03/16/2015 09:17 AM - Dominic Cleal

- translation missing: en.field_release set to 28

#2 - 04/27/2015 06:48 AM - Dominic Cleal

05/18/2024 1/3

#3 - 05/18/2015 08:53 PM - Anonymous

I tried to get @mediapath working for SUSE, but didn't succeed, maybe somebondy else can spot something, I was missing here:

```
\verb|diff --git a/app/controllers/unattended_controller.rb b/app/controllers/unattended_controller.rb | b/app/controllers/unattended_controllers/unattended_controllers/unattended_controllers/unattended_controllers/unattended_controllers/unattended_controllers/unattended_controllers/unattended_controllers/unattended_controllers/unattended_controllers/unattended_controllers/unattended_controllers/unattended_controllers/unattended_controllers/unattended_controllers/unattended_controllers/unattended_controllers/unattended_controllers/unattended_controllers/unattended_controllers/unattended_controllers/unattended_controllers/unattended_controllers/unattended_controllers/unattended_controllers/unattended_controllers/unattended_controllers/unattended_controllers/unattended_controllers/unattended_controllers/unattended_controllers/unattended_controllers/unattended_controllers/unattended_controllers/unattended_controllers/unattended_controllers/unattended_controllers/unattended_controllers/unattended_controllers/unattended_controllers/unattended_controllers/unattended_controllers/unattended_controllers/unattended_controllers/unattended_controllers/unattended_controllers/unattended_controllers/unattended_controllers/unattended_controllers/unattended_controllers/unattended
index da7eb0c..9cffe3b 100644
    -- a/app/controllers/unattended_controller.rb
 +++ b/app/controllers/unattended_controller.rb
@@ -236,6 +236,7 @@ class UnattendedController < ApplicationController
  def yast_attributes
         @mediapath = @host.operatingsystem.mediumpath @host
         def coreos_attributes
diff --git a/app/models/operatingsystems/suse.rb b/app/models/operatingsystems/suse.rb
index 1f8487f..cfcf8f5 100644
 --- a/app/models/operatingsystems/suse.rb
 +++ b/app/models/operatingsystems/suse.rb
 @@ -1,6 +1,11 @@
  class Suse < Operatingsystem
   PXEFILES = {:kernel => "linux", :initrd => "initrd"}
 + # Simple output of the media url
        def mediumpath(host)
              medium_uri(host).to_s
         def pxe_type
               "yast"
```

#4 - 05/19/2015 07:31 AM - The Foreman Bot

- Status changed from New to Ready For Testing
- Pull request https://github.com/theforeman/foreman/pull/2393 added
- Pull request deleted ()

#5 - 05/20/2015 02:25 AM - Dominic Cleal

- translation missing: en.field_release changed from 50 to 56

#6 - 05/20/2015 08:46 AM - Dominic Cleal

- Status changed from Ready For Testing to New
- Pull request added
- Pull request deleted (https://github.com/theforeman/foreman/pull/2393)

#7 - 06/15/2015 05:17 AM - Dominic Cleal

- translation missing: en.field_release deleted (56)

#8 - 12/14/2015 06:38 AM - Anonymous

- Related to Bug #12791: The architecture is not interpolated for the variable @host.url_for_boot(:initrd) on suse based systems added

#9 - 03/19/2016 04:49 PM - The Foreman Bot

- Status changed from New to Ready For Testing
- Assignee set to Anonymous
- Pull request https://github.com/theforeman/foreman/pull/3347 added

#10 - 03/22/2016 12:35 PM - Anonymous

- Related to Refactor #14319: Remove media_path template helper which is no longer used added

#11 - 03/30/2016 05:01 AM - Anonymous

05/18/2024 2/3

- Status changed from Ready For Testing to Closed
- % Done changed from 0 to 100

Applied in changeset <u>7aa342eabf33f96916f3061db313aecba46b0933</u>.

#12 - 03/30/2016 07:58 AM - The Foreman Bot

- Pull request https://github.com/theforeman/community-templates/pull/256 added

#13 - 03/31/2016 06:35 AM - Dominic Cleal

- translation missing: en.field_release set to 141

#14 - 07/15/2016 08:11 PM - Anonymous

- Related to Bug #15709: SLES doesn't get mediapath set in PXELinux config file added

05/18/2024 3/3